ACE LT 6000

DIESEL POWERED

Reliable 4-Light Diesel Mobile Lighting Tower - 7.0M Mast

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
23 ft (7.0 MTR)	4 x 400W LED (2,32,000 Lum...	44+ Hours (40L / 900ml/hr)	Up to 5000 sq. m

POWER & ENGINE SYSTEM	TECHNICAL SPECIFICATION DETAILS
Engine Model	KD15-441, Air Cooled
Engine Make	Rehlko (KOHLER)
Rated Power & Speed	8.1 BHP, RPM-3000
Alternator	Maccalte / NSM, 5 kVA Max, 240V, 50Hz, Singlephase, 17A Max, Brushless
Fuel Tank Capacity	40 L (Diesel), Canopy-Integrated
Fuel Consumption	Approx. 900 ml/hr (44+ Hours Runtime)
Lube Oil Capacity	1.5 Liters
Starting Battery	12V 35Ah with Heavy-Duty Starter
Silencer	Silencer Integrated into Canopy

LIGHTING SYSTEM & OPTICS	TECHNICAL SPECIFICATION DETAILS
Lights Configuration	4 x 400W LED Flood Lights (Total 1600W)
Total Brightness	2,32,000 Lumens
Beam Angle	Flood & Long Range Mix
Ingress Protection	IP-66 Weatherproof
Correlated Color Temp (CCT)	5000 - 6500K
Surge Protection	6 kV + 10 kV External
Connection Box	Upper Connection Box Provided
Electrical Certification	Certified CE Electrical Fittings
Illumination Coverage	Up to 5,000 sq. meters

TOWER & MAST ASSEMBLY	TECHNICAL SPECIFICATION DETAILS
Mast Height	7.0 m (Ground Level to Light)
Material & Thickness	Mild Steel, 3 mm Thick
Extension / Closing	Manual Mechanism Winch
Extension / Closing Time	Max. 5 Minutes Each
Rotation	359° Manual Rotation with Positive Lock
Wire Rope Metal	Stainless Steel
Wire Rope Size	6 mm

CHASSIS & MOBILITY	TECHNICAL SPECIFICATION DETAILS
Balancing Riggers	4 Nos. Collapsible Balancing Jacks
Tyres	2 Nos. Heavy Pneumatic Tyres
Overall Dimensions	Length: 1.4 - 1.5 m | Width: 1.1 - 1.2 m | Height: 2.4 - 2.5 m
Gross Weight	Approx. 700 kg
Recommended Features	Separate Miniature Circuit Breaker • Earthing Provision

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.

CONTROLS & SAFETY SYSTEMS	TECHNICAL SPECIFICATION DETAILS
Control Panel	Control System Mounted Inside Canopy
Hour Meter	Digital Hour Meter
Electrical Meters	Voltmeter & Amp. Meter
Fault Monitoring	Oil Alert and Fuel Fault Systems
Protections	Overload Protection, Earth Leakage Protection, Over Temperature Protection
Circuit Breakers	Each Light Has a Separate Miniature Circuit Breaker (MCB)
Emergency Controls	Emergency Stop Switch
Ventilation	Exhaust Fan

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- 4 x 400W LED Flood Lights delivering 2,32,000 lumens total brightness
- Illumination area coverage up to 5,000 square meters
- Rehlko (KOHLER) KD15-441 Air Cooled 8.1 BHP diesel engine running at 3000 RPM
- Maccalte/NSM 5 kVA brushless alternator (240V, 50Hz, 17A max single phase)
- 40-liter diesel tank capacity delivering over 44 continuous operating hours (approx 900 ml/hr)
- 7.0-meter vertical telescopic mast with 359° manual rotation and 6mm stainless steel wire rope
- Full safety suite: Earth Leakage, Overload, Over Temperature, Silencer & Exhaust Fan

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.