ACE PBLT 4000

BATTERY & PETROL OPERATED

Hybrid Battery & AC Mobile Light Tower - 4.0M Mast

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
13 ft (4.0 MTR)	6 x 60W LED (51,000 Lumens)	6 - 12 Hours (48V 60Ah)	3500 sq. m

POWER & BATTERY SPECIFICATIONS	TECHNICAL SPECIFICATION DETAILS
Power Source	360W, Output 230V
Battery Capacity	48V 60Ah
Battery Backup	High: 6 Hrs | Medium: 9 Hrs | Low: 12 Hrs
Socket for AC	Yes 16amp
Working Temperature	-40 deg. C to 90 deg. C

LIGHTING SYSTEM & PHOTOMETRICS	TECHNICAL SPECIFICATION DETAILS
No & Power of Light	6 x 60W - 360W Total
Light Source & Metal	LED, Aluminum Luminaire Metal
Brightness	51,000 Lumens
Luminous Efficacy	145 lm/w
Ingress Protection	IP66
Color Temperature (CCT)	6000K, CRI >= 75
Operating Temperature	-20 deg. C to +50 deg. C
Driver / Controller	Constant Power Mode
Dimming Function	Three Mode Type Only
Lux at 60m (360° Position)	1.5 Lux Approx
Lux at 60m (180° Position)	5.0 Lux Approx
BIS Certified	Yes

TOWER & ELEVATION ASSEMBLY	TECHNICAL SPECIFICATION DETAILS
Tower Type & Material	Telescopic type, Anodized Aluminum
Tower Segments	6 Minimum
Tower Height (Erected)	4000 mm Minimum
Tower Mast Height (Retract)	1050 mm Minimum
Mast Wall Thickness	1.55 mm Minimum
Erected & Retract Method	Manual
Erected & Retract Time	1.5 Minutes (Approx)
Rigger Opening	1200 mm +/- 100 mm in Diameter

DIMENSIONS, WEIGHT & LOGISTICS	TECHNICAL SPECIFICATION DETAILS
Wheels	02 Nos.
Length	500 mm +/- 10 mm
Width	485 mm +/- 10 mm
Height	1050 mm +/- 10 mm
Weight	50 Kg Max

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.

DIMENSIONS, WEIGHT & LOGISTICS	TECHNICAL SPECIFICATION DETAILS
Installation & Close Time	2 Minutes Max. (Approx)
Storage Box & Tool Kit	Storage Box Included | Tool Kit Included

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- Dual power: 360W source, 230V output with built-in 48V 60Ah high-capacity battery bank
- Battery runtime: High Mode: 6 Hrs | Medium Mode: 9 Hrs | Low Mode: 12 Hrs
- 6 x 60W LED luminaires delivering 51,000 lumens (145 lm/w, IP66, 6000K)
- 4000mm (4.0m) Anodized Aluminum 6-segment telescopic mast, retracts to 1050mm
- 16A AC socket for powering site tools or charging external equipment
- Constant power driver with 3-mode dimming function and BIS certification
- Compact footprint: 500 x 485 x 1050 mm, 50 kg max weight with 2 transport wheels
- Rapid 2-minute setup time; includes built-in storage box and toolkit

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.