ACE PLT 4000

PETROL OPERATED

Compact Portable Honda-Powered Petrol Light Tower - 4.0M Mast

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
13 ft (4.0 MTR Pneumatic)	6 x 80W LED (69,600 Lumens)	Approx 9 Hours (3.6L / 400...	4000 sq. m

ENGINE & GENERATOR SYSTEM	TECHNICAL SPECIFICATION DETAILS
GENSET (CPCB Approved)	Honda EP-1000, Petrol run, Air cooled, Rated output-750va
Tank Capacity / Consumption	3.6 Ltr (Petrol) / Fuel consumption approx- 400ml/hr
Lube Oil Capacity	360 ml
Socket for AC	Yes 16amp

LIGHTING SYSTEM & OPTICS	TECHNICAL SPECIFICATION DETAILS
No & Power of Light	6 x 80W - 480W Total
Light Source & Metal	LED, Aluminum Luminaire Metal
Brightness & Luminous Efficacy	69,600 Lumens | 145 lm/w
Ingress Protection	IP67 Weatherproof
Color Temperature (CCT)	5500K (+/- 500K), CRI >= 75
Operating Temperature	-20 deg. C to +50 deg. C
BIS Certification	BIS approved make embossed on LED lens as per IS 10322(part 5/ sec 5)
Driver Type	Constant Power potted driver with short circuit & high voltage cut off
Dimming Function	Rotary Type

TOWER & ELEVATION ASSEMBLY	TECHNICAL SPECIFICATION DETAILS
Tower Type & Material	Telescopic type, Anodized Aluminum
Tower Segments	6 Minimum
Tower Height (Erected)	4000 mm Minimum (4.0 Mtr)
Tower Mast Height (Retract)	1050 mm (+/- 50 mm)
Tower Mast Wall Thickness	1.55 mm Minimum
Erected & Retract Method	Pneumatic with Inbuilt Pump & Manual also
Erected & Retract Time	55 Seconds Maximum

MECHANICAL STRUCTURE & HARDWARE	TECHNICAL SPECIFICATION DETAILS
Main Structure Type	FRP 4 mm Minimum
Bottom Base Plate	3 mm Aluminum with Powder Coated
Top Bracket	MS Pipe (CR Pipe 25.4mm minimum) with Powder Coated
Rigger & Wheel Bracket	Mild Steel (CR) with Powder Coated
Bracket for LED (Cradle)	SS-304
Hardware	Stainless Steel (SS Nut-Bolt-Washer)

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- Honda EP-1000 generator (CPCB approved, petrol run, air cooled, rated output 750VA)
- 6 x 80W LED luminaires delivering 69,600 lumens with high efficacy (145 lm/w)
- 3.6-liter petrol tank with economical ~400 ml/hr consumption (~9 hours runtime)
- Telescopic Anodized Aluminum mast (6 segments), erected 4000mm, retract 1050mm
- Pneumatic erection with inbuilt pump and manual mechanism (55 seconds max)
- Rotary type dimming function with constant power potted driver and short circuit protection
- BIS approved make embossed on LED lens as per IS 10322 (part 5/ sec 5)
- Rugged structure: FRP 4mm minimum, 3mm aluminum base plate, SS-304 cradle, SS hardware

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.