Solar Powered Surveillance & Light Tower

SOLAR OPERATED

Clean Energy 24x7 Smart Surveillance & Mobile Lighting Tower

MAST HEIGHT	LIGHT / LUMENS	POWER / RUNTIME	COVERAGE AREA
20 - 30 ft (6.0 - 9.0 MTR)	3 x 300W High Efficiency (...	4 x 200Ah / 150Ah Gel (DC2...	1 x PTZ + 3 x Bullet (360°)

SOLAR POWER GENERATION & BATTERY BANK	TECHNICAL SPECIFICATION DETAILS
Solar Panels	3 x 300W High-Efficiency Monocrystalline Panels (900W Total Array)
Battery System	4 x 200Ah / 4 x 150Ah Gel Deep-Cycle Batteries (DC24V System)
Solar Charge Controller	Smart MPPT Controller with Overcharge & Low Voltage Disconnect

SURVEILLANCE & CAMERA ARRAY	TECHNICAL SPECIFICATION DETAILS
PTZ Network Camera	1 x 2MP High-Speed PTZ Dome (16x Optical Zoom, IR 100m, 360° Continuous Pan)
Bullet Perimeter Cameras	3 x 3MP Wide-Angle HD Bullet Cameras (IR 50m Night Vision)
Video Storage (NVR)	8-Channel Industrial NVR with 2 x 3TB Hard Drives
Networking & Connectivity	Industrial POE Switch | Optional 4G LTE Wireless Router

MAST & MECHANICAL STRUCTURE	TECHNICAL SPECIFICATION DETAILS
Mast Height	6.0 to 9.0 Meters (Manual / Electric / Hydraulic Options)
Wind Rating	100 km/h Tested Stability
Trailer Chassis	Single-Axle Trailer with 15" Wheels & 4 Stabilizer Jacks
Gross Weight	Approx. 500 kg
Overall Dimensions	2600 mm (L) x 1470 mm (W) x 2810 mm (H)

KEY ENGINEERING HIGHLIGHTS & COMPLIANCE

- 3 x 300W high-efficiency monocrystalline solar panels with tilting mechanism
- 4 x 200Ah / 4 x 150Ah deep-cycle gel batteries in a robust DC24V system
- 1 x 2MP PTZ network camera with 16x optical zoom, IR 100m, and 360° view
- 3 x 3MP HD bullet cameras providing 50m infrared night vision coverage
- Commercial 8-channel NVR with 2 x 3TB HDDs and industrial-grade POE switch
- 6.0 to 9.0-meter telescopic mast tested to 100 km/h wind rating speed
- Single-axle trailer chassis with 15" wheels, 4 manual stabilizer jacks, and 50mm ball hitch

© 2026 Ariselux Equipments. Technical specifications subject to continuous engineering innovation without notice.