

1. JSP MVC Architecture

1. What does MVC stand for in web application architecture?

- A) Model-View-Controller
- B) Model-View-Component
- C) Model-View-Creator
- D) Model-View-Collaborator

Answer: A) Model-View-Controller

2. Which component of the MVC architecture is responsible for handling user input?

- A) Model
- B) View
- C) Controller
- D) Servlet

Answer: C) Controller

3. In the MVC architecture, which component is responsible for retrieving data from the database?

- A) View
- B) Controller
- C) Model
- D) JSP

Answer: C) Model

4. What is the primary role of the View in MVC architecture?

- A) To process user input
- B) To display data to the user
- C) To manage application logic
- D) To handle database connections

Answer: B) To display data to the user

5. Which of the following is an example of a Model in a JSP application?

- A) user.jsp
- B) UserDAO
- C) UserController
- D) web.xml

Answer: B) UserDAO

2. JSP Life Cycle

6. What is the first phase of the JSP life cycle?

- A) Compilation Phase
- B) Translation Phase
- C) Initialization Phase
- D) Request Processing Phase

Answer: B) Translation Phase

7. During which phase is the JSP page converted into a servlet?

- A) Compilation Phase
- B) Translation Phase
- C) Class Loading Phase
- D) Destruction Phase

Answer: B) Translation Phase

8. Which method is called to initialize the JSP page?

- A) jspService()
- B) jspInit()
- C) jspDestroy()
- D) _jspService()

Answer: B) jspInit()

9. What happens during the Destruction Phase of a JSP page?

- A) The page is compiled.
- B) The page is translated into a servlet.
- C) The jspDestroy() method is called.
- D) The page is loaded into memory.

Answer: C) The jspDestroy() method is called.

3. JSP Directives

10. Which directive is used to define attributes that apply to the entire JSP page?

- A) Include Directive
- B) Taglib Directive
- C) Page Directive
- D) Error Page Directive

Answer: C) Page Directive

11. What is the purpose of the include directive in JSP?

- A) To include Java classes
- B) To include content from another file at translation time
- C) To define page-wide properties
- D) To handle errors

Answer: B) To include content from another file at translation time

12. Which attribute in the page directive specifies whether the page can handle errors?

- A) import
- B) contentType
- C) session
- D) isErrorPage

Answer: D) isErrorPage

4. JSP Implicit and Explicit Objects

13. Which of the following is NOT an implicit object in JSP?

- A) out
- B) request

- C) session
- D) database

Answer: D) database

14. What does the `out` implicit object represent?

- A) The current JSP page instance
- B) The client's request
- C) The response sent to the client
- D) Used to send output to the client

Answer: D) Used to send output to the client

15. Which implicit object represents the session for the user?

- A) request
- B) application
- C) session
- D) config

Answer: C) session

5. JSP Scriptlets

16. What is the purpose of JSP scriptlets?

- A) To define custom tags
- B) To embed Java code within a JSP page
- C) To handle errors
- D) To include other JSP files

Answer: B) To embed Java code within a JSP page

17. Which of the following is the correct syntax for a JSP scriptlet?

- A) `<% out.println("Hello"); %>`
- B)
- C) `jsp:scriptlet out.println("Hello"); </jsp:scriptlet>`
- D) `<%= out.println("Hello"); %>`

Answer: A) `<% out.println("Hello"); %>`

18. What is the output of the following scriptlet?

```
jsp
VerifyOpen In EditorRunCopy code
1<% int a = 5; int b = 10; out.println(a + b); %>
```

- A) 15
- B) 510
- C) 5
- D) 10

Answer: A) 15

6. JSP Expressions

19. What is the syntax for a JSP expression?

- A) `<% expression %>`

- B) <%= expression %>
- C) jsp:expressionexpression</jsp:expression>
- D)

Answer: B) <%= expression %>

20. Which of the following is a valid JSP expression?

- A) <%= 5 + 10 %>
- B) <% 5 + 10; %>
- C) jsp:expression5 + 10</jsp:expression>
- D)

Answer: A) <%= 5 + 10 %>

7. JSP Expression Language (EL)

21. What is the primary purpose of JSP Expression Language (EL)?

- A) To embed Java code in JSP
- B) To simplify data access in JSP pages
- C) To handle errors in JSP
- D) To define custom tags

Answer: B) To simplify data access in JSP pages

22. Which of the following is the correct syntax for using EL?

- A) <%= expression %>
- B) \${expression}
- C) jsp:expressionexpression</jsp:expression>
- D)

Answer: B) \${expression}

23. Which implicit object is used to access request parameters in EL?

- A) session
- B) request
- C) param
- D) application

Answer: C) param

8. JSP Scope

24. Which scope allows objects to be accessible only within the current JSP page?

- A) Request Scope
- B) Session Scope
- C) Application Scope
- D) Page Scope

Answer: D) Page Scope

25. What is the lifetime of an object stored in session scope?

- A) Until the page is processed
- B) Until the response is sent
- C) Until the session is invalidated

- D) Until the application is stopped
- Answer:** C) Until the session is invalidated

9. JSP Error Handling

26. Which attribute in the page directive specifies the error page for a JSP?

- A) isErrorPage
- B) errorPage
- C) contentType
- D) session

Answer: B) errorPage

27. What does the **isErrorPage** attribute indicate?

- A) The page can handle errors
- B) The page is a regular JSP page
- C) The page can include other files
- D) The page is a servlet

Answer: A) The page can handle errors

10. JSTL Core Functionalities

28. What is the purpose of the **c:if** tag in JSTL?

- A) To output data
- B) To iterate over a collection
- C) To conditionally include content
- D) To set a variable

Answer: C) To conditionally include content

29. Which JSTL tag is used to output data to the client?

- A) c:if
- B) c:choose
- C) c:out
- D) c:set

Answer: C) c:out

30. What does the **c:forEach** tag do?

- A) Outputs data
- B) Sets a variable
- C) Iterates over a collection
- D) Handles errors

Answer: C) Iterates over a collection