

Lecture 07: Process Creation and Termination



Vivek Kumar

Computer Science and Engineering

IIIT Delhi

vivekk@iiitd.ac.in

Last Lecture



- Protection rings (kernel and User mode) in Unix-like OS
- Interrupts and system call


Today's Class

- Process's life lessons

The OS Story Evolving So Far...

1. A **cook** (OS) manages a **kitchen** (*computer*)
2. The job of a cook is to do **cooking** (*execute binaries*) by reading **recipes** (*executable file*) in a **standard format** (*ELF*)
3. The cook has received recipe of a dish in **different files** (*relocatable files*). It will have to use a **stapler** (*linker*) to stitch these files to make a final recipe
4. The cook has to **store** (*load*) the **steps** (*instructions*) from the recipe in his memory to start cooking. The cook then execute instructions **one by one** (*call stack*) for cooking
5. The kitchen has gained a lot of popularity and have started receiving lot of recipes for cooking. The cook has hired several **helpers** (*processes*), where one helper cooks one recipe
6. To ensure the helpers don't fight for kitchen resources and make a mess, the ground rule is set that all helpers must talk to the head cook via a **hotline** (*interrupts*) if they need to access any kitchen resources
7. One of the helper got a huge recipe to cook. He decided to create an **identical twin** (*fork*) to let him own the **preparation** (*exec*) of one of the sub recipe

The Shell



- It is the first user process created by the OS after the bootup
- It runs in the user mode but it can create more processes by using system call
- Its main job is to execute user commands
 - Recall how we launched `./fib` executable in previous lecture

Shell Pseudocode (1/2)

```
void shell_loop() {  
    int status;  
    do {  
        printf("iiitd@possum:~$ ");  
        char* command = read_user_input();  
        status = launch(command);  
    } while(status);  
}
```

```
[iiitd@possum:~$ vi fib.c  
[iiitd@possum:~$ gcc fib.c  
[iiitd@possum:~$ ./a.out  
Fib(40) = 102334155
```

- Shell runs in an infinite loop and reads the user input to execute
- Should cease execution if it was unable to execute user command

Shell Pseudocode (2/2)

```
int launch (char *command) {  
    int status;  
    status = create_process_and_run(command);  
    return status;  
}
```

```
[iiitd@possum:~$ vi fib.c  
[iiitd@possum:~$ gcc fib.c  
[iiitd@possum:~$ ./a.out  
Fib(40) = 102334155
```

- The launch method accepts the user input (command name along with arguments to it)
- It will create a new process that would execute the user command and return execution status

A Process's Life Lessons

1. Processes can have children
2. Children should be obedient to their parent
3. Parent must follow the steps for good parenting
4. Children should not run their family business

Creating Child Processes (1/3)

```
int create_process_and_run(char* command) {
    int status = fork();
    if(status < 0) {
        printf("Something bad happened\n");
    } else if(status == 0) {
        printf("I am the child process\n");
    } else {
        printf("I am the parent Shell\n");
    }
    ....
    return 0;
}
```

- **fork** is a system call used for creating a new process
- Called once, but returns twice!
 - Return value in child process is zero, whereas child's process PID is returned in parent process
- It creates a replica of the parent process
 - Both the child and parent process are going to execute the same code with a minute difference
 - Copy-on-Write (COW) – Initially, both parent and child process have read-only access to parent's address space. Whichever process attempts a write on a memory page in parent's address space, it would get a copy of that page (lazy copy)
 - What about opened file descriptors?

Creating Child Processes (2/3)

```
int create_process_and_run(char* command) {  
    int status = fork();  
    if(status < 0) {  
        printf("Something bad happened\n");  
    } else if(status == 0) {  
        printf("I am the child process\n");  
    } else {  
        printf("I am the parent Shell\n");  
    }  
    ....  
    return 0;  
}
```

- Which of the two printf's would get printed first?
- The output is non-deterministic as the OS can decide on its own which one of the child or parent process should be in the "running" queue
 - Imagine there is single CPU
 - Will be discussed in details in later lectures on process scheduling

Creating Child Processes (3/3)

```
int global=0;
int create_process_and_run(char* command) {
    int status = fork();
    if(status < 0) {
        printf("Something bad happened\n");
    } else if(status == 0) {
        printf("I am the child process\n");
        global++;
    } else {
        printf("I am the parent Shell\n");
        sleep(2);
    }
    printf("Global value = %d\n",global);
    ....
    return 0;
}
```

- What value of the global variable will be printed?
- Although, the child is replica of the parent process, it has its own address space (heap, call stack, etc.) and registers
 - “Replica” here means both child and parent will run the exact same executable a.out immediately after calling fork (unless child and parent path are made separate as shown – if statement)
- Although we have made the parent to sleep for 2 seconds, it is not guaranteed that this duration is adequate for the child to move into running queue and complete its execution
- Inter-process communication is required for the updated global value to be seen by the parent
 - Next lecture!

A Process's Life Lessons (contd.)

1. Processes can have children
2. Children should be obedient to their parent
3. Parent must follow the steps for good parenting
4. Children should not run their family business

The Obedient Child

```
int create_process_and_run(char* command) {
    int status = fork();
    if(status < 0) {
        printf("Something bad happened\n");
    } else if(status == 0) {
        printf("I am the child process\n");
        exit(0);
    } else {
        printf("I am the parent Shell\n");
    }
    ....
    return 0;
}
```

- **exit** syscall allows to send a specific termination code (exit status) from a child process to the parent upon termination
 - “signal” is sent to the parent (inter-process communication)
 - In case of abnormal termination of child, the exit status is generated and send by the kernel
- exit carries out process cleanup – reclaiming memory, flushes buffers, closing fds, etc.
 - Any difference with “return” in C?
- But how the parent can get the exit status (**next slide**)?
 - Remember child is not going to return to the parent just like a callee method returns to a caller method

The Act of Good Parenting

```
int create_process_and_run(char* command) {
    int status = fork();
    if(status < 0) {
        printf("Something bad happened\n");
        exit(0);
    } else if(status == 0) {
        printf("I am the child (%d)\n",getpid());
    } else {
        int ret;
        int pid = wait(&ret);
        if(WIFEXITED(ret)) {
            printf("%d Exit =%d\n",pid,WEXITSTATUS(ret));
        } else {
            printf("Abnormal termination of %d\n",pid);
        }
        printf("I am the parent Shell\n");
    }
    return 0;
}
```


- **wait** and **waitpid** allows the parent process to block until the child process terminates
 - **wait** will block only for the first child, whereas **waitpid** can be used for a specific child
 - Returns the child's PID
 - Used for retrieving exit status from child
- Will there be deterministic execution of printf's from parent and child processes (notice there is no sleep)?
- Good parents avoid making their child as **Zombies or Orphan**
 - Child is zombie when it has terminated but has its exit code remaining in the process table as it is waiting for the parent to read the status
 - **Orphaned** children outliving their parent's lifetime are adopted by the mother-of-all-processes (**init**)

Child Should Not Run Family Business

```
int create_process_and_run(char* command) {
    int status = fork();
    if(status < 0) {
        printf("Something bad happened\n");
        exit(0);
    } else if(status == 0) {
        printf("I am the child process\n");
        char* args[2] = {"./fib", "40"};
        execv(args[0], args);
        printf("I should never print\n");
    } else {
        printf("I am the parent Shell\n");
    }
    ....
    return 0;
}
```

- Main goal for creating a child process is to let it live its own free life without depending on its parent
 - The child won't let go off the parent's property (code) until its forced to call **exec**
- An exec calls the OS loader internally that loads the ELF file with its command line argument as specified in the argument list
- There are seven different versions of exec which are collectively referred as exec function

exec Behind the Curtain



- It's only job is to construct the process's address space
 - Unload current process address space (segments)
 - Read ELF file from the disk
 - Create the user part of the address space lazily
 - E.g., space for `.data` will be allocated only after some global variable is accessed during program execution from the `.text` segment
- Note that PID remains the same after the process calls `exec`

Next Lecture

- Inter-process communication