Pontificia Universidad Católica de Chile
Escuela de Ingeniería
Departamento de Ciencias de la Computación

IIC2343 – Arquitectura de Computadores

Ayudantía 2

Profesor: Yadran Eterovic

Ayudantes: Daniel Leal (dlleal@uc.cl), Jessica Hormazabal (jyhormazabal@uc.cl)

Preguntas

1. **Assembly**

   a) Cargue los valores 5 y 17 en los registros $s1 y $s2. Considere registros de 1 byte.

   b) Utilizando la arquitectura ISA MEEP MEEP, programe una multiplicación en *assembly* entre dos números guardados en memoria. Considere que los números a multiplicar están en las direcciones 8 y 9, mientras que el resultado desea guardarse en la dirección 13.

   c) Utilizando la arquitectura ISA MEEP MEEP, programe en *assembly* un código que le permita sumar N números pares positivos desde el número P_0 en adelante. Asuma que N y P_0 están guardados en la memoria RAM en las direcciones 13 y 21, respectivamente. Guarde el valor final en la dirección 4 de la memoria. Comente si lo encuentra necesario.

2. **Anexos**

MIPS assembly language

Category	Instruction	Example	Meaning	Comments
Arithmetic	add	`add $s1,$s2,$s3`	$s1 = $s2 + $s3	Three register operands
	subtract	`sub $s1,$s2,$s3`	$s1 = $s2 – $s3	Three register operands
	add immediate	`addi $s1,$s2,20`	$s1 = $s2 + 20	Used to add constants
Data transfer	load word	`lw $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Word from memory to register
	store word	`sw $s1,20($s2)`	Memory[$s2 + 20] = $s1	Word from register to memory
	load half	`lh $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Halfword memory to register
	load half unsigned	`lhu $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Halfword memory to register
	store half	`sh $s1,20($s2)`	Memory[$s2 + 20] = $s1	Halfword register to memory
	load byte	`lb $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Byte from memory to register
	load byte unsigned	`lbu $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Byte from memory to register
	store byte	`sb $s1,20($s2)`	Memory[$s2 + 20] = $s1	Byte from register to memory
	load linked word	`ll $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Load word as 1st half of atomic swap
	store condition. word	`sc $s1,20($s2)`	Memory[$s2+20]=$s1;$s1=0 or 1	Store word as 2nd half of atomic swap
	load upper immed.	`lui $s1,20`	$s1 = 20 * 2^{16}	Loads constant in upper 16 bits
Logical	and	`and $s1,$s2,$s3`	$s1 = $s2 & $s3	Three reg. operands; bit-by-bit AND
	or	`or $s1,$s2,$s3`	$s1 = $s2 | $s3	Three reg. operands; bit-by-bit OR
	nor	`nor $s1,$s2,$s3`	$s1 = ~ ($s2 | $s3)	Three reg. operands; bit-by-bit NOR
	and immediate	`andi $s1,$s2,20`	$s1 = $s2 & 20	Bit-by-bit AND reg with constant
	or immediate	`ori $s1,$s2,20`	$s1 = $s2 | 20	Bit-by-bit OR reg with constant
	shift left logical	`sll $s1,$s2,10`	$s1 = $s2 << 10	Shift left by constant
	shift right logical	`srl $s1,$s2,10`	$s1 = $s2 >> 10	Shift right by constant
Conditional branch	branch on equal	`beq $s1,$s2,25`	if ($s1 == $s2) go to PC + 4 + 100	Equal test; PC-relative branch
	branch on not equal	`bne $s1,$s2,25`	if ($s1!= $s2) go to PC + 4 + 100	Not equal test; PC-relative
	set on less than	`slt $s1,$s2,$s3`	if ($s2 < $s3) $s1 = 1; else $s1 = 0	Compare less than; for `beq`, `bne`
	set on less than unsigned	`sltu $s1,$s2,$s3`	if ($s2 < $s3) $s1 = 1; else $s1 = 0	Compare less than unsigned
	set less than immediate	`slti $s1,$s2,20`	if ($s2 < 20) $s1 = 1; else $s1 = 0	Compare less than constant
	set less than immediate unsigned	`sltiu $s1,$s2,20`	if ($s2 < 20) $s1 = 1; else $s1 = 0	Compare less than constant unsigned
Unconditional jump	jump	`j 2500`	go to 10000	Jump to target address
	jump register	`jr $ra`	go to $ra	For switch, procedure return
	jump and link	`jal 2500`	$ra = PC + 4; go to 10000	For procedure call

Figura 1: ISA de un computador MIPS



Figura 2: ISA de un computador MEEP MEEP