

# **CS 235: Artificial Intelligence**

## **Week 2**

### **Blind (Uninformed) Search**

**Dr. Moumita Roy**



**CSE Dept., IITG**

Reference: <http://ai.stanford.edu/~latombe/cs121/2011/schedule.htm>

# Simple Problem-Solving-Agent Agent Algorithm


1.  $s_0 \leftarrow \text{sense/read initial state}$
2.  $GOAL? \leftarrow \text{select/read goal test}$
3.  $Succ \leftarrow \text{read successor function}$
4.  $\text{solution} \leftarrow \text{search}(s_0, GOAL?, Succ)$
5.  $\text{perform}(\text{solution})$

# Search Tree




Note that some states may be visited multiple times


# Search Nodes and States



# Search Nodes and States



# Data Structure of a Node




Depth of a node N  
= length of path from root to N  
(depth of the root = 0)

# Node expansion

The **expansion** of a node N of the search tree consists of:


- 1) Evaluating the successor function on  $STATE(N)$
- 2) Generating a child of N for each state returned by the function

**node generation  $\neq$  node expansion**



# Fringe of Search Tree

- The **fringe** is the set of all search nodes that haven't been expanded yet





# Search Strategy

- The **fringe** is the set of all search nodes that haven't been expanded yet
- The fringe is implemented as a **priority queue** FRINGE
  - INSERT(node,FRINGE)
  - REMOVE(FRINGE)
- The ordering of the nodes in FRINGE defines the **search strategy**

# Search Algorithm #1

## SEARCH#1

1. If GOAL?(initial-state) then return initial-state
2. INSERT(initial-node,FRINGE)
3. Repeat:
  - a. If empty(FRINGE) then return failure
  - b.  $N \leftarrow \text{REMOVE}(\text{FRINGE})$  Expansion of N
  - c.  $s \leftarrow \text{STATE}(N)$
  - d. For every state  $s'$  in  $\text{SUCCESSORS}(s)$ 
    - i. Create a new node  $N'$  as a child of  $N$
    - ii. If GOAL?( $s'$ ) then return path or goal state
    - iii. INSERT( $N'$ ,FRINGE)

# Performance Measures

- **Completeness**

A search algorithm is complete if it finds a solution whenever one exists

[What about the case when no solution exists?]

- **Optimality**

A search algorithm is optimal if it returns a minimum-cost path whenever a solution exists

- **Complexity**




It measures the time and amount of memory required by the algorithm

# Blind vs. Heuristic Strategies

- **Blind** (or **un-informed**) strategies do not exploit state descriptions to order FRINGE. They only exploit the positions of the nodes in the search tree
- **Heuristic** (or **informed**) strategies exploit state descriptions to order FRINGE (the most "promising" nodes are placed at the beginning of FRINGE)

# Example




For a **blind strategy**,  $N_1$  and  $N_2$  are just two nodes (at some position in the search tree)



Goal state

# Example

For a **heuristic strategy** counting the number of misplaced tiles,  $N_2$  is more promising than  $N_1$




# Blind Strategies

- Breadth-first
    - Bidirectional
  - Depth-first
    - Depth-limited
    - Iterative deepening
  - Uniform-Cost  
(variant of breadth-first)
- } Arc cost = 1
- } Arc cost =  $c(\text{action}) \geq \epsilon > 0$

# Breadth-First Strategy

New nodes are inserted **at the end** of FRINGE




FRINGE = (1)



# Breadth-First Strategy


New nodes are inserted **at the end** of FRINGE



FRINGE = (2, 3)

# Breadth-First Strategy


New nodes are inserted **at the end** of FRINGE



FRINGE = (3, 4, 5)

# Breadth-First Strategy

New nodes are inserted **at the end** of FRINGE



FRINGE = (4, 5, 6, 7)

# Important Parameters

- 1) Maximum number of successors of any state  
→ branching factor  $b$  of the search tree
- 2) Minimal length ( $\neq$  cost) of a path between the initial and a goal state  
→ depth  $d$  of the shallowest goal node in the search tree

# Evaluation

- $b$ : branching factor
- $d$ : depth of shallowest goal node
- Breadth-first search is:
  - Complete? Not complete?
  - Optimal? Not optimal?

# Evaluation

- $b$ : branching factor
- $d$ : depth of shallowest goal node
- Breadth-first search is:
  - Complete
  - Optimal if step cost is 1
- Number of nodes generated:  
???

# Evaluation

- $b$ : branching factor
- $d$ : depth of shallowest goal node
- Breadth-first search is:
  - Complete
  - Optimal if step cost is 1
- Number of nodes generated:  
 $1 + b + b^2 + \dots + b^d = ???$

# Evaluation

- $b$ : branching factor
- $d$ : depth of shallowest goal node
- Breadth-first search is:
- **Complete**
  - **Optimal** if step cost is 1
- Number of nodes generated:  
$$1 + b + b^2 + \dots + b^d = (b^{d+1} - 1) / (b - 1) = O(b^d)$$
- → Time and space complexity is  $O(b^d)$
- When we can apply goal test? Node generation/Node expansion?



# Big O Notation

$g(n) = O(f(n))$  if there exist two positive constants  $a$  and  $N$  such that:

for all  $n > N$ :  $g(n) \leq a \times f(n)$

# Time and Memory Requirements

d	# Nodes	Time	Memory
2	111	.01 msec	11 Kbytes
4	11,111	1 msec	1 Mbyte
6	$\sim 10^6$	1 sec	100 Mb
8	$\sim 10^8$	100 sec	10 Gbytes
10	$\sim 10^{10}$	2.8 hours	1 Tbyte
12	$\sim 10^{12}$	11.6 days	100 Tbytes
14	$\sim 10^{14}$	3.2 years	10,000 Tbytes

Assumptions:  $b = 10$ ; 1,000,000 nodes/sec; 100bytes/node

# Time and Memory Requirements


d	# Nodes	Time	Memory
2	111	.01 msec	11 Kbytes
4	11,111	1 msec	1 Mbyte
6	$\sim 10^6$	1 sec	100 Mb
8	$\sim 10^8$	100 sec	10 Gbytes
10	$\sim 10^{10}$	2.8 hours	1 Tbyte
12	$\sim 10^{12}$	11.6 days	100 Tbytes
14	$\sim 10^{14}$	3.2 years	10,000 Tbytes

Assumptions:  $b = 10$ ; 1,000,000 nodes/sec; 100bytes/node

# Remark

If a problem has no solution, breadth-first may run for ever (if the state space is infinite or states can be revisited arbitrary many times)


1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	



1	2	3	4
5	6	7	8
9	10	11	12
13	15	14	

# Bidirectional Strategy

2 fringe queues: FRINGE1 and FRINGE2




Time and space complexity is  $O(b^{d/2}) \ll O(b^d)$   
if both trees have the same branching factor  $b$

Question: What happens if the branching factor is different in each direction?


# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE



# Depth-First Strategy


New nodes are inserted **at the front** of FRINGE






# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE




# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE



# Depth-First Strategy

New nodes are inserted **at the front** of FRINGE





# Evaluation

- $b$ : branching factor
- $d$ : depth of shallowest goal node
- $m$ : maximal depth of a leaf node
- Depth-first search is:
  - Complete?
  - Optimal?

# Evaluation

- **b**: branching factor
  - **d**: depth of shallowest goal node
  - **m**: maximal depth of a leaf node
  - Depth-first search is:
    - Complete only for finite search tree
    - Not optimal
  - Number of nodes generated (worst case):  
 $1 + b + b^2 + \dots + b^m = O(b^m)$
  - Time complexity is  $O(b^m)$
  - Space complexity is  $O(bm)$  [or  $O(m)$ ]
- [Reminder: Breadth-first requires  $O(b^d)$  time and space]

# Depth-Limited Search

- Depth-first with **depth cutoff**  $k$  (depth at which nodes are not expanded)
- Three possible outcomes:
  - Solution
  - Failure (no solution)
  - **Cutoff (no solution within cutoff)**

# Iterative Deepening Search

Provides the best of both breadth-first and depth-first search


IDS

For  $k = 0, 1, 2, \dots$  do:


    Perform depth-first search with  
    depth cutoff  $k$

    (i.e., only generate nodes with depth  $\leq k$ )


# Iterative Deepening



# Iterative Deepening



# Iterative Deepening



# Performance

- Iterative deepening search is:
  - Complete
  - Optimal if step cost = 1
- Time complexity is:  
 $(d+1)(1) + db + (d-1)b^2 + \dots + (1)b^d = O(b^d)$
- Space complexity is:  $O(bd)$  or  $O(d)$



# Number of Generated Nodes (Breadth-First & Iterative Deepening)

$d = 5$  and  $b = 2$

BF	ID
1	$1 \times 6 = 6$
2	$2 \times 5 = 10$
4	$4 \times 4 = 16$
8	$8 \times 3 = 24$
16	$16 \times 2 = 32$
32	$32 \times 1 = 32$
63	120

$$120/63 \sim 2$$

# Number of Generated Nodes (Breadth-First & Iterative Deepening)

$d = 5$  and  $b = 10$

BF	ID
1	6
10	50
100	400
1,000	3,000
10,000	20,000
100,000	100,000
111,111	123,456

$123,456 / 111,111 \sim 1.111$

# Comparison of Strategies

- Breadth-first is complete and optimal, but has high space complexity
- Depth-first is space efficient, but is neither complete, nor optimal
- Iterative deepening is complete and optimal, with the same space complexity as depth-first and almost the same time complexity as breadth-first

# Revisited States


No

Few


Many

search tree is finite



search tree is infinite



8-queens



assembly  
planning



8-puzzle and robot navigation