

```
sharangubbala@Sharans-MacBook-Air CD % flex uppercase.1
gcc lex.yy.c -o uppercase
[./uppercase
Enter the input string:
adsybqr
ADSYBQR
■
```

```
sharangubbala@Sharans-MacBook-Air ~ % /Users/sharangubbala/Downloads/CD/email ;
exit;
Enter the email: sharangubbala@gmail.com
It is valid
```

```
t sharangubbala@Sharans-MacBook-Air ~ % /Users/sharangubbala/Downloads/CD/mobile ;
exit;
Enter the mobile number: 9113193933
Mobile number is valid
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex comment.1
gcc lex.yy.c -o comment
[./comment sample.c
#include <stdio.h>
```

```
int main()
{
```

```
    printf("Hello");
    return 0;
```

```
}The number of comment lines = 0
```

```
sharangubbala@Sharans-MacBook-Air CD % /Users/sharangubbala/Downloads/CD
flex number.1
gcc lex.yy.c -o number
./number
```

```
zsh: permission denied: /Users/sharangubbala/Downloads/CD
```

```
Enter numbers:
```

```
-10 013 -202
```

```
Negative number = -10
```

```
Positive number = 013
```

```
Negative number = -202
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex html.1
```

```
gcc lex.yy.c -o html
[./html
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex identifier.1
```

```
gcc lex.yy.c -o identifier
[./identifier
```

```
Enter a string: sharan123
```

```
sharan123 is IDENTIFIER
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex vowels.l
gcc lex.yy.c -o vowels
[./vowels
Enter the string: hello worf
```

```
Number of vowels = 3
Number of consonants = 6
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex linewidth.l
gcc lex.yy.c -o linewidth
[./linewidth
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex commentcheck.l
gcc lex.yy.c -o commentcheck
[./commentcheck
Enter the input: hsasdr7c
hsasdr7c is NOT A COMMENT
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex digit.l
gcc lex.yy.c -o digit
[./digit
Enter the input: 1234567
1234567 is DIGIT
```

```
sharangubbala@Sharans-MacBook-Air CD % cd /Users/sharangubbala/Downloads/CD
flex macroheader.l
gcc lex.yy.c -o macroheader
[./macroheader < test.c
<stdio.h>
<stdlib.h>
```

```
MAX 100
MIN 10
PI 3.14
```

```
int main()
{
    return 0;
}
Number of macros defined = 3
Number of header files included = 2
```