

1.username

```
sharanaya@DESKTOP-TPK9V: ~$ nano username.c
sharanaya@DESKTOP-TPK9V: ~$ gcc username.c -o username
sharanaya@DESKTOP-TPK9V: ~$ ./username
Enter your name:sharanya
Welcome sharanya
sharanaya@DESKTOP-TPK9V: ~$ |
```

```
GNU nano 8.7.1
#include<stdio.h>
int main()
{
char name[30];
printf("Enter your name:");
scanf("%s",name);
printf("Welcome %s\n",name);
return 0;
}
```

2.welcome

```
sharanaya@DESKTOP-TPK9V: ~$ nano welcome.c
sharanaya@DESKTOP-TPK9V: ~$ gcc welcome.c -o welcome
sharanaya@DESKTOP-TPK9V: ~$ ./welcome
Welcome to operating system
sharanaya@DESKTOP-TPK9V: ~$ |
```

```
GNU nano 8.7.1
#include<stdio.h>
int main()
{
printf("Welcome to operating system\n");
return 0;
}
```

3.processid

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano processid.c
sharanaya@DESKTOP-TPK9V3Q:~$ gcc processid.c -o processid
sharanaya@DESKTOP-TPK9V3Q:~$ ./processid
Process ID=722
sharanaya@DESKTOP-TPK9V3Q:~$ |
```

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano processid.c
GNU nano 8.7.1
#include<stdio.h>
#include<unistd.h>
int main()
{
printf("Process ID=%d\n",getpid());
return 0;
}
```

4.fork

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano processid.c
sharanaya@DESKTOP-TPK9V3Q:~$ nano fork.c
sharanaya@DESKTOP-TPK9V3Q:~$ gcc fork.c -o fork
sharanaya@DESKTOP-TPK9V3Q:~$ ./fork
Hello
Hello
sharanaya@DESKTOP-TPK9V3Q:~$ |
```

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano fork.c
GNU nano 8.7.1
#include<stdio.h>
#include<unistd.h>
int main()
{
fork();
printf("Hello\n");
return 0;
}
```

5.double fork

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano doublefork.c
sharanaya@DESKTOP-TPK9V3Q:~$ gcc doublefork.c -o doublefork
sharanaya@DESKTOP-TPK9V3Q:~$ ./doublefork
Hello
Hello
Hello
Hello
sharanaya@DESKTOP-TPK9V3Q:~$ |
```

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano doublefork.c
GNU nano 8.7.1
#include<stdio.h>
#include<unistd.h>
int main()
{
fork();
fork();
printf("Hello\n");
return 0;
}
```

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano parentchild.c
sharanaya@DESKTOP-TPK9V3Q:~$ gcc parentchild.c -o parentchild
sharanaya@DESKTOP-TPK9V3Q:~$ ./parentchild
I am ParentProcess
I am Child Process
sharanaya@DESKTOP-TPK9V3Q:~$ |
```

```
sharanaya@DESKTOP-TPK9V3Q: ~ × + ▾
GNU nano 8.7.1
#include<stdio.h>
#include<unistd.h>
int main()
{
    pid_t pid;
    pid=fork();
    if(pid==0)
    {printf("I am Child Process\n");
    }
    else
    {
    printf("I am ParentProcess\n");
    }
}
```

7.parent

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano parent.c
sharanaya@DESKTOP-TPK9V3Q:~$ gcc parent.c -o parent
sharanaya@DESKTOP-TPK9V3Q:~$ ./parent
Parent PID = 1053
Child PID = 1054
Parent PID = 1054
sharanaya@DESKTOP-TPK9V3Q:~$ |
```

```
sharanaya@DESKTOP-TPK9V3Q: ~ × + ∨
GNU nano 8.7.1
#include<stdio.h>
#include<unistd.h>
int main()
{
    pid_t pid;
    pid=fork();
    if(pid==0)
    {
        printf("Child PID = %d\n",getpid());
        printf("Parent PID = %d\n",getpid());
    }
    else
    {
        printf("Parent PID = %d\n",getpid());
    }
}
```

8.wait

```
sharanaya@DESKTOP-TPK9V3Q:~$ nano wait.c
sharanaya@DESKTOP-TPK9V3Q:~$ gcc wait.c -o wait
sharanaya@DESKTOP-TPK9V3Q:~$ ./wait
Child Running
Parent Running After Child
sharanaya@DESKTOP-TPK9V3Q:~$ |
```

```
GNU nano 8.7.1
#include<stdio.h>
#include<unistd.h>
#include<sys/wait.h>
int main()
{
    pid_t pid;
    pid=fork();
    if(pid==0)
    {
        printf("Child Running\n");
    }
    else
    {
        wait(NULL);
        printf("Parent Running After Child\n");
    }
    return 0;
}
```