

```
#include <stdio.h>
```

```
int main() {
```

```
int i, j, x;
```

```
printf("Enter no. of rows");
```

```
scanf("%d", &x);
```

```
for (i=0; i<x; i++) {
```

```
for (j=0; j<x; j++) {
```

```
printf("%c", 'A' + x - i - j);
```

```
printf("\n");
```

```
}
```

```
}
```

2) #include <stdio.h>

```
int main() {
```

```
int i, j, rows;
```

```
printf("Enter no. of rows:");
```

```
scanf("%d", &rows);
```

```
char left = 'A' + rows - 1;
```

```
char right = left - 1;
```

```
for (i=1; i<=rows; i++) {
```

```
printf("%c", left - i + 1);
```

```
}
```

```
return 0;
```

```
}
```

3) #include <stdio.h>

```
int main() {
```

```
int i, j, x;
```

```
printf("Enter no. of rows:");
```

```
scanf("%d", &x);
```



```

for (i=0 ; i<x ; i++) {
    for (j=0 ; j<x ; j++) {
        printf("%d ", i+j);
    }
    printf("\n");
}

```

```

4 #include <stdio.h>
int main () {
    int i, j, x;
    printf("Enter no of rows:");
    scanf("%d", &x);
    for (i=1 ; i<=x ; i++) {
        for (j=1 ; j<=x ; j++) {
            printf("%d", i*i);
        }
        printf("\n");
    }
}

```

```

5. #include <stdio.h>
int main () {
    int i, j, x;
    printf("Enter no of rows:");
    scanf("%d", &x);
    for (i=1 ; i<=x ; i++) {
        for (j=1 ; j<=x ; j++) {
            if (j%2 == 0)
                printf("%d", i*i+i);
            else
                printf("%d", i*i);
        }
    }
    printf("\n");
}

```



```
#include <stdio.h>
```

```
int main () {
```

```
int i, j, x;
```

```
printf ("Enter no. of rows: ");
```

```
scanf ("%d", &x);
```

```
for (i=0; i<x; i++) {
```

```
for (j=0; j<x; j++) {
```

```
if (x%2 == 0)
```

```
printf ("%d", 'A');
```

```
else
```

```
printf ("%c", 'A');
```

```
}
```

```
printf ("\n");
```

```
}
```

```
}
```

```
7) #include <stdio.h>
```

```
int main () {
```

```
int i, j, rows;
```

```
printf ("Enter no. of rows: ");
```

```
scanf ("%d", &rows);
```

```
int num = rows * rows;
```

```
char ch = 'A' + rows * row;
```

```
for (i=0; i<=rows; i++) {
```

```
for (j=0; j<rows; j++) {
```

```
if (j%2 == 0)
```

```
printf ("%d", num--);
```

```
else
```

```
printf ("%c", ch--);
```

```
}
```

```
printf ("\n");
```

```
}
```

```
}
```


8. #include <stdio.h>

int main () {

int i, j, x;

printf ("Enter no. of rows: ");

scanf ("%d", &x);

for (i = 0; i < x; i++) {

if (i % 2 == 1) {

for (j = 0; j < x; j++)

printf ("%c", 'c' + j);

}

else {

for (j = 0; j < x; j++)

printf ("%c", 'c' + x - j);

}

printf ("\n");

}

return 0;

}

9. #include <stdio.h>

int main () {

int rows, i, j, val;

printf ("Enter no. of rows: ");

scanf ("%d", &rows);

for (i = 0; i < rows; i++) {

for (j = 0; j < rows; j++) {

val = rows + i + j;

if ((i + j) % 2 == 0)

printf ("%c", 'A' + val);

else

printf ("%c", 'a' + val);

}

printf ("\n");

}


```

10. #include <stdio.h>

int main() {
    int x, i, j;
    printf("Enter no. of rows: ");
    scanf("%d", &x);
    for (i = 0; i < x; i++) {
        for int val = x - (i/2) * 2;
        for (j = 0; j < x; j++) {
            if (j < x/2)
                printf("%d", val);
            else
                printf("%d", val - (i % 2));
        }
        printf("\n");
    }
}

```