

Practical - 13

1- #include <stdio.h>

int main() {

int i, j, x;

printf("Enter no. of rows:");

scanf("%d", &x);

for (i = 1; i <= x; i++) {

for (j = 1; j <= i; j++) {

printf("%d", j);

}

printf("\n");

}

return 0;

}

```

2) #include <stdio.h>
int main () {
    int i, j, x;
    printf ("Enter no. of rows. ");
    scanf ("%d", &x);
    for (i = 0; i < x; i++) {
        for (j = x; j > x - i; j--) {
            printf ("%d", j);
        }
        printf ("\n");
    }
}

```

```

3) #include <stdio.h>
int main () {
    int i, j, x;
    printf ("Enter no. of rows. ");
    scanf ("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = 1; j <= i; j++) {
            printf ("%c", 'A' + (i + j - 2));
        }
        printf ("\n");
    }
}

```

```

4) #include <stdio.h>
int main () {
    int i, j, x;
    printf ("Enter no. of rows. ");
    scanf ("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = 1; j <= i; j++) {

```

```

        printf ("%d", x * j);
    }
    printf ("\n");
}
return 0;
}

```

5) #include <stdio.h>

```
int main () {
```

```
    int i, j, x;
```

```
    printf ("Enter no. of rows: ");
```

```
    scanf ("%d", &x);
```

```
    for (i = 1; i <= x; i++) {
```

```
        for (j = 1; j <= x; j++) {
```

```
            printf ("%d", i * j);
```

```
        }
```

```
    printf ("\n");
```

```
}
```

```
}
```

6) #include <stdio.h>

```
int main () {
```

```
    int i, j, x;
```

```
    printf ("Enter no. of rows: ");
```

```
    scanf ("%d", &x);
```

```
    for (i = x; i >= 1; i--) {
```

```
        for (j = 1; j <= i; j++) {
```

```
            printf ("%d", i);
```

```
        }
```

```
    printf ("\n");
```

```
}
```

```
}
```

```

75 #include <stdio.h>
int main() {
    int i, j, x;
    printf("Enter no. of rows ");
    scanf("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = 1; j <= x - i + 1; j++) {
            printf("%d", j);
        }
        printf("\n");
    }
}

```

```

8) #include <stdio.h>
int main() {
    int i, j, x;
    printf("Enter no. of rows ");
    scanf("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = i; j <= x; j++) {
            printf("%d", j);
        }
        printf("\n");
    }
}

```

```

9) #include <stdio.h>
int main() {
    int i, j, x;
    printf("Enter no. of rows ");
    scanf("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = x; j >= 1; j--) {

```

```

        printf("%c", 'A' + j);
    }
    printf("\n");
}

```

```

10) #include <stdio.h>
int main() {
    int i, j, x;
    printf("Enter no. of rows ");
    scanf("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = i; j <= x; j++) {
            ch = 'A' + (i + j - 2);
            if (j % 2 == 1)
                printf("%d", ch);
            else
                printf("%c", ch);
        }
        printf("\n");
    }
}

```