

Practical 8

```

1) #include <stdio.h>
int main() {
    int i, j, x;
    char ch = 'A';
    printf("Enter no. of rows: ");
    scanf("%d", &x);
    for (i = 0; i < x; i++) {
        for (j = 0; j < i; j++) {
            printf("%c", ch);
            ch++;
        }
        printf("\n");
    }
    return 0;
}
    
```

```

2) #include <stdio.h>
int main() {
    int i, j, x;
    printf("Enter no. of rows: ");
    scanf("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = i; j <= x; j++) {
            printf("%d", j);
        }
        printf("\n");
    }
}
    
```

```

3) #include <stdio.h>
int main() {
    int i, j, x;
    printf("Enter no. of rows: ");
    scanf("%d", &x);
    for (i = 1; i <= x; i++) {
        for (j = 1; j <= i; j++) {
            printf("%d", j);
        }
        printf("\n");
    }
}
    
```

```

for (i=x; i>=1; i--) {
    for (j=0; j<=x; j++) {
        printf (" %c ", 'A'+i);
    }
    printf ("\n");
}

```

4) #include <stdio.h>

```

int main () {
    int i, j, x;
    printf ("Enter no. of rows:");
    scanf ("%d", &x);
    for (i=1; i<=x; i++) {
        for (j=1; j<=i; j++) {
            if (i%2 == 1) {
                printf ("%d", i);
                i = i + 2;
            }
        }
        printf ("\n");
    }
}

```

5) #include <stdio.h>

```

int main () {
    int i, j, x;
    printf ("Enter no. of rows:");
    scanf ("%d", &x);
    for (i=1; i<=x; i++) {
        if (i%2 == 0) {
            for (j=x; j>=1; j--) {
                printf ("%d", j);
            }
        }
        else {
            for (j=1; j<=i; j++) {
                printf ("%d", j);
            }
        }
    }
}

```

```
printf("\n");
```

```
for (i = 1; i <= x; i++) {
    if (i % 3 == 0) {
        for (j = 1; j <= x; j++) {
            printf("%d", i);
        }
        printf("\n");
    }
}
```

```
2) for (i = 1; i <= x; i++) {
    for (j = 1; j <= x; j++) {
        if (j % 2 == 1)
            printf("*", j);
        else
            printf("#", j);
    }
}
```

```
8) for (i = 1; i <= x; i++) {
    for (j = 1; j <= x; j++) {
        printf("A %d", j);
    }
    printf("\n");
}
```