

FISSO Product Brochure

V2021JAN



26.1 Articulated arms



26.2 Strato set

The company Baitella AG, based in Zurich, is the world's leading provider of user-friendly, individualized holding system solutions with central clamping unit. **FISSO** articulated arms are successfully used worldwide as a quality product for applications in the medical and industrial sectors.

Table of contents

26.1 Articulated arms	26.1
26.1.1 Strato Line	26.1
26.1.2 Strato μ -Line	26.2
26.1.3 Classic Line	26.2
26.1.4 Base Line	26.3
26.2 Strato set	26.3
26.2.1 Strato XS-13	26.3

26.1 Articulated arms



26.1.1 STRATO LINE



Selection parameters

Parameters	Min	Max
Overall Height	185 mm	390 mm
Radius of Movement	130 mm	180 mm
Fine Adjustment	Ø 8	Ø 8
Holding Strength	150 N	1000 N

Industries it caters to

General Industry

Product application

Profile Measurement

Industrial Testing Equipment

Fibre Optic and LED-Light Holder

The Strato Line series is available with red anodized arm sections. These are equipped with a zero play microfing adjustment.

26.1 Articulated arms (continued)

26.1.2 STRATO μ -LINE



Selection parameters

Parameters	Min	Max
Overall Height	185 mm	390 mm
Radius of Movement	130 mm	180 mm
Fine Adjustment	Ø 8	Ø 8
Holding Strength	150 N	1000 N

Industries it caters to

General Industry

Product application

Profile Measurement

Industrial Testing Equipment

Fibre Optic and LED-Light Holder

The Strato μ -Line series is the expansion of strato series. These are extremely high precision 3D articulated arms.

26.1.3 CLASSIC LINE



Selection parameters

Parameters	Min	Max
Overall Height	185 mm	630 mm
Radius of Movement	130 mm	1210 mm
Fine Adjustment	Ø 8	Ø 8
Holding Strength	150 N	1500 N

Industries it caters to

General Industry

Product application

Profile Measurement

Industrial Testing Equipment

Fibre Optic and LED-Light Holder

The Classic Line series contains articulated arms with chrome plated arm sections. These are equipped with a zero play microfine adjustment.

26.1 Articulated arms (continued)

26.1.4 BASE LINE



Selection parameters

Parameters	Min	Max
Overall Height	277 mm	453 mm
Fine Adjustment	Ø 8	Ø 8
Holding Strength	300 N	750 N

Industries it caters to

General Industry

Product application

Profile Measurement

Industrial Testing Equipment

Fibre Optic and LED-Light Holder

The Base Line series has gauging arms with high degree of stability. These are equipped with precise microfne adjustment.

26.2 Strato set

26.2.1 STRATO XS-13



Selection parameters

Parameters	Min	Max
Radius of Movement	130 mm	130 mm
Fine Adjustment	Ø 8	Ø 8
Holding Strength	-	300

Industries it caters to

General Industry

Product application

Profile Measurement

Industrial Testing Equipment

Fibre Optic and LED-Light Holder

The Strato Set is a carrying case useful for on-site inspection. It is available with microfne adjustment and dial indicator.