

INTRODUCTION TO SQL

22

Why SQL?

23

- SQL is a very-high-level language.
 - ▣ Structured Query Language
 - ▣ Say “what to do” rather than “how to do it.”
 - ▣ Avoid a lot of data-manipulation details needed in procedural languages
 - ▣ Database management system figures out “best” way to execute query.
 - ▣ Called “query optimization.”

Credit: Renee J. Miller

23

Database Schemas in SQL

24

- SQL is primarily a query language, for getting information from a database.
 - ▣ **Data manipulation language (DML)**
- But SQL also includes a *data-definition* component for describing database schemas.
 - ▣ **Data definition language (DDL)**

24

Select-From-Where Statements

25

SELECT desired attributes
FROM one or more tables
WHERE condition about tuples of the tables

25

Our Running Example

26

- Our SQL queries will be based on the following database schema.

- Underline indicates key attributes.

Beers(name, manf)

Bars(name, addr, license)

Drinkers(name, addr, phone)

Likes(drinker, beer)

Sells(bar, beer, price)

Frequents(drinker, bar)

26

Example

27

- Using Beers(name, manf), what beers are made by Anheuser-Busch?

```
SELECT name
FROM Beers
WHERE manf = 'Anheuser-Busch';
```

27

Result of Query

28

name
Bud
Bud Lite
Michelob
...

The answer is a relation with a single attribute, name, and tuples with the name of each beer by Anheuser-Busch, such as Bud.

28

Meaning of Single-Relation Query

29

- Begin with the relation in the FROM clause.
- Apply the selection indicated by the WHERE clause.
- Apply the extended projection indicated by the SELECT clause.

29

Operational Semantics - General


30

- Think of a *tuple variable* visiting each tuple of the relation mentioned in FROM.
- Check if the tuple assigned to the tuple variable satisfies the WHERE clause.
- If so, compute the attributes or expressions of the SELECT clause using the components of this tuple.

30

Operational Semantics

31



31

Example

32

- What beers are made by Anheuser-Busch?
- ```
SELECT name
FROM Beers
WHERE manf = 'Anheuser-Busch';
```
- OR:
- ```
SELECT t.name
FROM Beers t
WHERE t.manf = 'Anheuser-Busch';
```

Note: these are identical queries.

32

* In SELECT clauses

33

- When there is one relation in the FROM clause, * in the SELECT clause stands for "all attributes of this relation."
 - Example: Using *Beers(name, manf)*:
- ```
SELECT *
FROM Beers
WHERE manf = 'Anheuser-Busch';
```

33

## Result of Query:

34

| name     | manf           |
|----------|----------------|
| Bud      | Anheuser-Busch |
| Bud Lite | Anheuser-Busch |
| Michelob | Anheuser-Busch |
| ...      | ...            |

Now, the result has each of the attributes of Beers.

34

## Renaming Attributes

35

- If you want the result to have different attribute names, use "AS <new name>" to rename an attribute.

- **Example:** Using **Beers(name, manf):**

```
SELECT name AS beer, manf
FROM Beers
WHERE manf = 'Anheuser-Busch'
```

35

## Result of Query:

36

| beer     | manf           |
|----------|----------------|
| Bud      | Anheuser-Busch |
| Bud Lite | Anheuser-Busch |
| Michelob | Anheuser-Busch |
| ...      | ...            |

36

## Expressions in SELECT Clauses

37

- Any valid expression can appear as an element of a SELECT clause.

- **Example:** Using **Sells(bar, beer, price):**

```
SELECT bar, beer,
 price*95 AS priceInYen
FROM Sells;
```

37

## Result of Query

38

| bar   | beer   | priceInYen |
|-------|--------|------------|
| Joe's | Bud    | 285        |
| Sue's | Miller | 342        |
| ...   | ...    | ...        |

38

## Example: Constants as Expressions

39

- Using `Likes(drinker, beer)`:

```
SELECT drinker,
 'likes Bud' AS whoLikesBud
FROM Likes
WHERE beer = 'Bud';
```

39

## Result of Query

40

| drinker | whoLikesBud |
|---------|-------------|
| Sally   | likes Bud   |
| Fred    | likes Bud   |
| ...     | ...         |

40

## Complex Conditions in WHERE Clause

41

- Boolean operators AND, OR, NOT.
- Comparisons =, <>, <, >, <=, >=.

41

## Example: Complex Condition

42

- Using `Sells(bar, beer, price)`, find the price Joe's Bar charges for Bud:

```
SELECT price
FROM Sells
WHERE bar = 'Joe's Bar' AND
 beer = 'Bud';
```

42