

ENTITY-RELATIONSHIP MODEL

7

Overview of Database Design

8

- *Conceptual design:*
 - ▣ What are the *entities* and *relationships* in the enterprise?
 - ▣ What information about these entities and relationships should we store in the database?
 - ▣ What are the *integrity constraints* or *business rules* that hold?

8

Purpose of E/R Model

9

- The Entity/Relationship (E/R) model allows us to sketch database schema designs.
 - ▣ Includes some constraints
- Schema designs are pictures called *entity-relationship diagrams*.
- *Later:* convert E/R designs to relational DB designs.

Credit: Renee J. Miller

9

Framework for E/R

10

- Design is a necessity.
- Management know they want a database, but they don't know what they want in it.
- Sketching the key components is an efficient way to develop a working database.

10

Entity Sets

11

- **Entity** = “thing” or object.
- **Entity set** = collection of similar entities.
 - ▣ Similar to a class in object-oriented languages.
- **Attribute** = property of an entity set.
 - ▣ Attributes are simple values, e.g. integers or character strings, not structs, sets, etc.
 - ▣ Each attribute has a *domain*.

11

E/R Diagrams


12

- In an entity-relationship diagram:
 - ▣ Entity set = rectangle.
 - ▣ Attribute = oval, with a line to the rectangle representing its entity set.
 - ▣ Notation varies: some textbooks represents attributes within the (entity) rectangle

12

Example

13



- Entity set **Beers** has two attributes, *name* and *manf* (manufacturer).
- Each **Beers** entity has values for these two attributes, e.g. (Bud, Anheuser-Busch)

13


Relationships

14

- A **relationship** connects two or more entity sets.
- It is represented by a diamond, with lines to each of the entity sets involved.

14

Example: Relationships



15

Relationship Set

- 16
- The current “value” of an entity set is the set of entities that belong to it.
 - ▣ **Example:** the set of all bars in our database.
 - The “value” of a relationship is a **relationship set**, a set of tuples with one component for each related entity set.

16

Example: Relationship Set

- 17
- For the relationship **Sells**, we might have a relationship set like:

Bar	Beer
Joe's Bar	Bud
Joe's Bar	Miller
Sue's Bar	Bud
Sue's Bar	Pete's Ale
Sue's Bar	Bud Lite


17

Multiway Relationships

- 18
- Sometimes, we need a relationship that connects more than two entity sets.
 - Suppose that drinkers will only drink certain beers at certain bars.
 - ▣ Our three binary relationships **Likes**, **Sells**, and **Frequent** do not allow us to make this distinction.
 - ▣ But a 3-way relationship would.

18

Example: 3-Way Relationship



19

A Typical Relationship Set

20

Bar	Drinker	Beer
Joe's Bar	Ann	Miller
Sue's Bar	Ann	Bud
Sue's Bar	Ann	Pete's Ale
Joe's Bar	Bob	Bud
Joe's Bar	Bob	Miller
Joe's Bar	Cal	Miller
Sue's Bar	Cal	Bud Lite


20

Many-Many Relationships

- 21
- Focus: **binary** relationships, such as **Sells** between **Bars** and **Beers**.
 - In a **many-many relationship**, an entity of either set can be connected to many entities of the other set.
 - ▣ E.g., a bar sells many beers; a beer is sold by many bars.

21

In Pictures:



many-many

Note: each line is an instance of the binary relationship

22


Many-One Relationships

23

- Some binary relationships are *many -one* from one entity set to another.
- Each entity of the first set is connected to at most one entity of the second set.
- But an entity of the second set can be connected to zero, one, or many entities of the first set.

In Pictures:

24



many-one


(Partial) Function on entity set

24

Example: Many-One Relationship

25

- Favourite*, from *Drinkers* to *Beers* is many-one.
- A drinker has at most one favourite beer.
- But a beer can be the favorite of any number of drinkers, including zero.




25

One-One Relationships

26

- In a *one-one relationship*, each entity of either entity set is related to at most one entity of the other set.
- Example:** Relationship *Best-seller* between entity sets *Manfs* (manufacturer) and *Beers*.
 - A beer is the best seller for 0 or 1 manufacturers, and no manufacturer can have more than one best-seller (assume no ties).



26

Representing “Multiplicity”


27

- Show a many-one relationship by an arrow entering the “one” side.
 - ▣ “at most one”
 - Show a one-one relationship by arrows entering both entity sets.
- Rounded (open) arrow** = “exactly one,” i.e., each entity of the first set is related to exactly one entity of the target set.

27

Example: Many-One Relationship


28



28

Example: Many-One Relationship

29



29

Example: One-One Relationship

30


- Consider **Best-seller** between **Manfs** and **Beers**.
- Some beers are not the best-seller of any manufacturer
- But a beer manufacturer has to have a best-seller.



30

In the E/R Diagram

31



31

Participation Constraints


32

- Does every student have to take a course?
 - If so, this is a participation constraint: the participation of Students in Enrolled is said to be *total (vs. partial)*.
 - Every *sid* value in Students table must appear in a row of the Enrolled table (with a non-null *sid* value!)
- Textbook notation: total participation represented by a thick (bolded) line originating from entity

32

Example: Many-One Relationship


33




33

Example: Many-One Relationship

34



34



35