



HEAVY DUTY MULTI-PURPOSE GREASE AEROSOL

White Aerosol Lithium Grease Spray

WHITE LITHIUM GREASE

NON-STAINING • WATER RESISTANT

Net Weight: 14 ounces (397 grams)

**KEEP OUT OF REACH OF CHILDREN
DANGER: EXTREMELY FLAMMABLE**
VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

See back panel for additional precautionary statements.

HEAVY DUTY MULTI-PURPOSE GREASE is a white lithium based all weather lubricant. It penetrates like an oil, then sets up to a thick grease. The operating temperature range is -40°F to 350°F . This grease is excellent for use on gears, chains, sprockets, linkages, slides, bearings, hinges, cranks, pinions, worms, overhead door tracks and rollers, auto and truck doors, hoods and trunk lids.

DIRECTIONS FOR USE:

Shake well before using. Make sure surface or part to be lubricated is clean and dry. Spray on part or surface from a distance of 6 to 8 inches. Repeat as necessary.

DANGER: EXTREMELY FLAMMABLE

VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

Do not expose to heat, sparks or open flame. Use in a well-ventilated area. Do not store at temperatures above 120°F . Do not puncture or incinerate container. Avoid contact with eyes and prolonged contact with skin.

FIRST AID:

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting.

IF INHALED: Remove person to fresh air. If breathing has stopped, administer artificial respiration. Without medical advice, do not use mouth-to-mouth method if victim has inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet for additional safety instructions.

Health	1
Flammability	4
Reactivity	0
Personal Protection	X

HMIS®
Severe 4
Serious 3
Moderate 2
Slight 1
Minimal 0

NFPA
Extreme
High
Moderate
Slight
Insignificant



This Product Contains

Petroleum Distillate	64742-52-5
Aliphatic Petroleum Solvent	64742-89-8
Synthetic Isoparaffinic Hydrocarbon	64742-47-8
Liquefied Petroleum Gas	68476-86-8

CAS No.

Petroleum Distillate	64742-52-5
Aliphatic Petroleum Solvent	64742-89-8
Synthetic Isoparaffinic Hydrocarbon	64742-47-8
Liquefied Petroleum Gas	68476-86-8