Safety Data Sheet



SECTION 1: Product and company identification

Product name : Early Harvest Air Freshener

Use of the substance/mixture : Aerosol

Odorant

Product code : 859501

Company : Share Corporation

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



CHEUS

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Precautionary statements (GHS-US) : Keep away from heat, sparks, open flames, hot surfaces. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
propane	(CAS No) 74-98-6	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
ethanol	(CAS No) 64-17-5	2.5 - 10	Flam. Liq. 2, H225 STOT SE 3, H336

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation

: Remove the victim into fresh air. Artificial respiration and/or oxygen if necessary. Do not apply mouth-to-mouth resuscitation. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve of other proper respiratory medical device. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact

: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. For minor skin contact, avoid spreading material on unaffected skin.

First-aid measures after eye contact

: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Date of issue: 10/2/2015 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 1 of 6

Safety Data Sheet

First-aid measures after ingestion : Get medical advice/attention. Rinse mouth with water. Do not induce vomiting without medical

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Direct contact with the eyes is likely irritating.

Symptoms/injuries after inhalation : No effects known. Symptoms/injuries after skin contact : No effects known.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Keep watching the victim. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Foam. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Contents under pressure. Pressurized container: may burst if heated.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Use water spray or fog for

cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor

nozzles, if possible. If not, withdraw and let fire burn out.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air.

May accumulate in low areas e.g. close to the ground. Eliminate every possible source of ignition.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment. DO NOT touch spilled material.

Emergency procedures : Ventilate the area thoroughly, especially low lying areas (basements, work pits etc.). Advice local

authorities if considered necessary.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Prevent runoff from entering drains, sewers or waterways. Avoid discharge to the environment. Advice local authorities if considered necessary. Stop leak if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate every possible source of ignition. Keep combustibles (wood, paper, oil, etc.) away from

spilled material. Stop leak if safe to do so. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent the product from entering drains or confined areas. For further information refer to section 8: Exposure-controls/personal protection"".

Methods for cleaning up : Take up liquid spill into absorbent material. Following product recovery, flush area with water.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Do not use if spray button is missing or defective. Do not spray on a naked flame or any

incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Do not re-use empty containers. Avoid breathing dust, fume, gas, mist, spray, vapors. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Do not discharge the waste into the

drain.

Hygiene measures : Use good personal hygiene practices.

 Date of issue: 10/2/2015
 Revision date: 02/26/2015
 Version: 1.0
 P GHS SDS
 Page 2 of 6

Safety Data Sheet



7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush. Take precautionary measures against

static discharge.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Refrigerate. Keep

away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials : Heat sources. Sources of ignition.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

Storage area : Aerosol, Category 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)				
ACGIH	ACGIH TWA (ppm)	1000 ppm		
ACGIH	ACGIH STEL (ppm)	1000 ppm		
propane (74-98-6)	propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm		
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm		
ethanol (64-17-5)				
ACGIH	ACGIH STEL (ppm)	1000 ppm		
ACGIH	Remark (ACGIH)	URT irr		

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Ventilation rates should be matched to conditions. If

applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Personal protective equipment : Gloves. Protective clothing. Safety glasses. Use appropriate personal protective equipment when

risk assessment indicates this is necessary.







Hand protection : Protective gloves.

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-

supplied respirator.

Thermal hazard protection : Use appropriate personal protective equipment when risk assessment indicates this is necessary.

Consumer exposure controls : When using do not smoke. Use good personal hygiene practices. Take off contaminated clothing

and wash before reuse. Wash hands and other exposed areas with mild soap and water before eat,

drink or smoke and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. Cloudy. Liquid.

Odor : characteristic
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : 212 °F estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available

Date of issue: 10/2/2015 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 3 of 6

Safety Data Sheet



Explosive properties : No data available Oxidizing properties : No data available Vapor pressure No data available Relative density : No data available Relative vapor density at 20 °C : No data available Specific gravity / density : 0.877 g/ml estimated Solubility : Not determined. Log Pow No data available Log Kow : No data available : No data available Auto-ignition temperature Decomposition temperature No data available Viscosity : No data available No data available Viscosity, kinematic Viscosity, dynamic : No data available VOC content : Not Determined

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Risk of ignition.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Skin corrosion/irritation

Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Not classified

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
ATE CLP (oral)	10740.000 mg/kg body weight

Serious eye damage/irritation : Not classified Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Dizziness. Direct contact with the eyes is likely irritating.

Symptoms/injuries after inhalation : No effects known. Symptoms/injuries after skin contact : No effects known.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

use.

 Date of issue: 10/2/2015
 Revision date: 02/26/2015
 Version: 1.0
 P GHS SDS
 Page 4 of 6

Safety Data Sheet

Likely routes of exposure : Skin and eyes contact.;Inhalation



SECTION 12: Ecological information

12.1. Toxicity

ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	9300 mg/l (48 h; Daphnia magna)
LC50 fish 2	13000 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)
Threshold limit other aquatic organisms 1	65 mg/l (72 h; Protozoa)
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa; Growth rate)
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda; Growth rate)

12.2. Persistence and degradability

ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O□/g substance
Chemical oxygen demand (COD)	1.70 g O □/g substance
ThOD	2.10 g O □/g substance
BOD (% of ThOD)	0.43 % ThOD

12.3. Bioaccumulative potential

ethanol (64-17-5)	
BCF fish 1	1 (72 h; Cyprinus carpio)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with

local/regional/national/international regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Empty containers should be taken for recycle, recovery or waste in accordance with local

regulation. Handle empty containers with care because residual vapors are flammable. Handle

unclean empty containers as full ones. Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

: 75 kg

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

: 150 kg

DOT Vessel Stowage Location

: A

Date of issue: 10/2/2015 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 5 of 6

Safety Data Sheet DOT Vessel Stowage Other

: 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

,

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : Aerosols

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No.(IĀTA) : UN1950
Proper Shipping Name (IATA) : Aerosols

Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

butane (106-97-8)			
Not listed on SARA Section 313 (Speci	fic toxic chemical listings)		
propane (74-98-6)			
Not listed on SARA Section 313 (Speci	fic toxic chemical listings)		

California Proposition 65 - This product does not contain substances known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:


Compressed gas	Gases under pressure Compressed gas
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H336	May cause drowsiness or dizziness

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Date of issue: 10/2/2015 Revision date: 02/26/2015 Version: 1.0 P GHS SDS Page 6 of 6