

FUEL AID PLUS

Multifunctional Gasoline Fuel Additive

Form: Liquid

Color: Amber

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble

(in mineral spirits): Soluble

VOC Content (% by weight): 100%

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): 118°F

Specific Gravity: 0.86 ± 0.05 g/cm³

Density: 7.18 ± 0.05 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S.

Aromatic Hydrocarbon 64742-95-6

Hydrocarbyl Amine Proprietary

Hydrocarbon Solvent Proprietary

Petroleum Naphtha..... 64742-94-5

Polyether Amine Proprietary

Other Uses...

- **State/County Highway Garages**
- **Police Departments**
- **Fire Departments**
- **Truck Lines**
- **Car Rentals**
- **School Bus Garages**
- **Marinas**
- **Bus Lines**

DIRECTIONS: Use 8 to 12 ounces of FUEL AID PLUS for every 20 gallons of fuel. In bulk storage tanks, use 2 to 3 gallons per 1000 gallons of gasoline.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	2
Flammability	Moderate	2	Moderate	Flammability	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection	Minimal	0	Insignificant	Special Precautions	None