



FREE FLOAT OWS

CONCENTRATED CLEANER AND DEGREASER

DESIGNED EXCLUSIVELY FOR USE IN OIL/WATER SEPARATOR SYSTEMS.
CONTAINS NO ACIDS, ALKALIES, OR BUTYL SOLVENTS.

WARNING

Causes skin irritation. Causes serious eye irritation.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ☐ 1 ☐ 5 ☐ 20 ☐ 35 ☐ 55 Gallon(s)

FREE FLOAT OWS



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**

WARNING:

Causes skin irritation. Causes serious eye irritation.
Wash thoroughly after handling. Wear eye protection,
protective clothing, protective gloves.

IF ON SKIN:

Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

Dispose in a safe manner in accordance with local/national
regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

WARNING:

This product contains, or may contain, trace quantities
of a substance(s) known to the state of California to
cause cancer and/or reproductive toxicity.

Avoid costly sewer discharge violations and eliminate environmental
contamination with **FREE FLOAT OWS**. This concentrated
cleaner and degreaser has been developed specifically for use
in Oil/Water Separator (OWS) systems.

Most detergents emulsify fats, oils, and grease (FOG) and
hold them in suspension indefinitely, allowing the FOG to
pass through OWS systems and into the sewer lines. Other
detergents require drastic pH adjustments or other chemical
processes in order for the detergent to release the emulsified FOG.

FREE FLOAT OWS has been formulated with specially selected
surfactants that effectively and efficiently lift dirt, grease, oil,
and other surface contamination from any water washable
surface. Once collected and sent to an OWS system, **FREE
FLOAT OWS** easily releases the emulsified FOG, allowing it to
coalesce into a separate oil layer, while dirt and other debris
are filtered out in the silt chamber or other applicable filtration method.

DIRECTIONS

Inject 2 to 4 ounces of **FREE FLOAT OWS** per gallon of water
into the wash system. Wash surface, allow cleaner to work for
a few minutes, then rinse. Collect and send rinsewater through
OWS system. Collect free floating FOG using absorbent pads
or brooms. If bioremediation is chosen as a means of handling
FOG disposal, **FREE FLOAT OWS** will not interfere with the
action of the microbes or otherwise inhibit the bioremediation process.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Surfactant (Proprietary); Sodium
Tripolyphosphate (7758-29-4); Sodium Metasilicate (6834-92-0);
Ethoxylated Alcohols Phosphate Ester (68130-47-2)



Please Recycle.

0414.040715