



GRAPHITE LUBRICANT

GRAPHITE LUBRICANT SPRAY

REDUCES FRICTION & HEAT

DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer (Inhalation). May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

See back panel for further cautions and first aid instructions.

NET WEIGHT: 12 oz. (340 g)

GRAPHITE LUBRICANT lubricates and protects at the same time. It penetrates deeply to eliminate friction and squeaks and leaves a hard, dry, protective film of graphite. The no-mess **GRAPHITE LUBRICANT** film will not wash off and provides lubrication at high or low temperature extremes.



DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer (Inhalation). May cause damage to organs through prolonged or repeated exposure.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames or sparks. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe fume, gas, mist, spray, vapors. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves.

RESPONSE:

IF SWALLOWED: Immediately call a doctor, a POISON CENTER.
IF ON SKIN: Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention. Take off contaminated clothing and wash before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. **If exposed or concerned:** Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell. Get medical advice/attention if you feel unwell. Do NOT induce vomiting.

STORAGE:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations.

INGREDIENTS/CAS#:

Toluene (108-88-3); Petroleum gases, liquefied (68476-86-8); Crystalline Silica (14808-60-7)

NFPA® RATINGS:

Health: 3; Flammability: 2; Reactivity: 0

DIRECTIONS:

Shake well before using. Hold nozzle 8 to 12 inches from the surface to be treated. Spray **GRAPHITE LUBRICANT** to cover surface with a light, even mist. For hard-to-reach areas, insert extension tube in spray tip. Clean the spray nozzle thoroughly after each use by inverting can and pressing valve for 2 to 3 seconds.

Note: Suitable for use with operating temperatures ranging from -100 °F. to +800 °F.

WARNING:

This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

Sold by:



Please Recycle.

8211.051515

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com