

# DEGREASER

## Aerosol Flush-Off Solvent

**Form:** Liquid

**Color:** Colorless

**Odor:** Petroleum Distillate

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** N/D

**Viscosity (CPS at 70°F):** >40

**Flash Point (ASTM D-7821):** 120°F

**Specific Gravity:**  $0.80 \pm 0.05 \text{ g/cm}^3$

**Density:**  $6.68 \pm 0.05 \text{ lbs/gal}$

**Storage Stability (at 70°F):** 1 year

### Ingredients

### C.A.S. #

Kerosene .....	8008-20-6
Mineral Spirits .....	8052-41-3
2-Butoxyethanol .....	111-76-2
Butane (Propellant) .....	106-97-8
Propane (Propellant) .....	74-98-6

### Other DEGREASER Uses

- **Rust Proof Remover**
- **Floor Degreaser**
- **Aircraft Degreaser**
- **Parts Wash**
- **Wood Floor Cleaner/Stripper**
- **Barbecue Cleaner**
- **Printing Ink Remover**
- **Transmission Cleaner**

**DIRECTIONS:** Hold can upright with nozzle 10 to 12 inches from the surface to be cleaned. Spray DEGREASER to thoroughly cover deposits and allow it to penetrate for up to 10 minutes. Flush away loosened deposits with water spray. For thick deposits, brush or scrape away excess to help speed removal then repeat application. **NOTE:** DEGREASER should not be used on asphalt floor tiles. Test painted surfaces, plastics and other floor types by spraying on an inconspicuous area prior to using.

HMIS				NFPA	
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	2
Flammability .....	Moderate	2	Moderate	Flammability.....	4
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection .....	Minimal	0	Insignificant	Special Precautions .....	None