



**CONCRETE, WOOD & DECK SEALER**

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: □ 1 □ 5 □ 20 □ 35 □ 55 Gallon(s)**



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**



**DISPOSAL:**

Offer empty container for recycling. If recycling is not available, discard container in trash.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**WARNING:**

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

**NFPA® RATINGS**

Health: 0; Flammability: 0; Reactivity: 0

**INGREDIENTS/CAS #:**

Water (7732-18-5); Fluoropolymer (Proprietary); 2-methylpentane-2,4-diol (107-41-5); 2-methyl-2H-isothiazol-3-one (2682-20-4); 1,2-benzisothiazol-3-(2H)-one (2634-33-5)



Please Recycle.

0125.060215

Share's **BLOCKADE** invisible concrete protector uses a high-tech, fluoropolymer coating that resists both oil and water-based spills. It won't discolor the surface, change the appearance, or turn yellow, making **BLOCKADE** a truly invisible product. The invisible protection prevents spill absorption and staining, keeping surfaces attractive and easy to clean. It will protect concrete and other porous surfaces such as stone, quarry tile, brick and mortar, grout and granite, and many more.

**DIRECTIONS:**

**BLOCKADE** is easy to apply using a brush, medium nap roller, or low pressure sprayer. The surface to be treated does not need any special treatment but it must be dry and water, oil, and dust free to allow proper penetration of the product. Allow the sealer to impregnate the surface for 5-10 minutes and then remove the excess from the surface (this is the most important step because if the sealer dries on the surface it will leave a residue). Allow to dry for 2 hours. Re-apply using the same procedure and then remove the excess. The polymer will cure in approximately 24 hours at 60°F. After curing, place a small droplet of water on the surface to check that it beads up and this will indicate that the sealer has satisfactorily cured.

**Pre-Cleaning Recommendations (if needed):**

Any of Share's water soluble cleaners or degreasers.

**Coverage:** Blockade will cover approximately 250 to 500 square feet per gallon depending on the concrete porosity and two coats are recommended. Typically a 5 gallon pail will seal 1,000 square feet of poured concrete using two applications.

**Life Expectancy:** 2-3 years under normal conditions.