

IL Metal Working Lubricant/Coolant

Safety Data Sheet



SECTION 1: Product and company identification

Product name : IL Metal Working Lubricant/Coolant
Use of the substance/mixture : Lubricant.
Product code : 030301
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224 - USA
T (414) 355-4000
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: Causes skin irritation
Causes serious eye irritation

Precautionary statements (GHS-US)

: Wash thoroughly after handling
Wear eye protection, protective clothing, protective gloves
If on skin: Wash with plenty of soap and water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If skin irritation occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash before reuse

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
2-aminoethanol, ethanolamine	(CAS No) 141-43-5	1-5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove the victim into fresh air.
First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

IL Metal Working Lubricant/Coolant

Safety Data Sheet



- | | |
|--------------------------------------|--|
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Rinse mouth with water. Do NOT induce vomiting. |

4.2. Most important symptoms and effects, both acute and delayed

- | | |
|--------------------------------------|--|
| Symptoms/injuries after inhalation | : None under normal use. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |
| Symptoms/injuries after eye contact | : Causes serious eye irritation. |
| Symptoms/injuries after ingestion | : Gastrointestinal complaints. Nausea. Vomiting. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- | | |
|------------------------------|------------------------------------|
| Suitable extinguishing media | : All extinguishing media allowed. |
|------------------------------|------------------------------------|

5.2. Special hazards arising from the substance or mixture

- | | |
|------------|--|
| Reactivity | : Thermal decomposition may produce oxides of carbon and nitrogen. |
|------------|--|

5.3. Advice for firefighters

- | | |
|--------------------------------|--|
| Firefighting instructions | : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : Isolate from fire, if possible, without unnecessary risk. |
|------------------|---|

6.1.1. For non-emergency personnel

- | | |
|----------------------|--|
| Protective equipment | : Protective goggles. Gloves. Protective clothing. |
| Emergency procedures | : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area. |

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Use personal protective equipment as required. |
| Emergency procedures | : Stop leak if safe to do so. Stop release. Ventilate area. |

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Contain released substance, pump into suitable containers. |
| Methods for cleaning up | : This material and its container must be disposed of in a safe way, and as per local legislation. |

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. |
| Hygiene measures | : Wash thoroughly after handling. Wash contaminated clothing before reuse. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|-------------------------------|---|
| Technical measures | : Comply with applicable regulations. |
| Storage conditions | : Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| Incompatible products | : acids. Strong oxidizers. |
| Prohibitions on mixed storage | : KEEP SUBSTANCE AWAY FROM: (strong) acids. |
| Storage area | : Meet the legal requirements. Store in a cool area. Store in a dry area. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

IL Metal Working Lubricant/Coolant

Safety Data Sheet



8.2. Exposure controls

Personal protective equipment

: Safety glasses. Protective clothing. Gloves. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear. Gold. brown.
Odor	: slight
Odor threshold	: No data available
pH	: 9 - 11
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.05 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: < 6 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition may produce oxides of carbon and nitrogen.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

acids. Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

IL Metal Working Lubricant/Coolant

Safety Data Sheet



Acute toxicity : Not classified

2-aminoethanol, ethanolamine (141-43-5)

LD50 oral rat	1720 mg/kg female
LD50 dermal rabbit	1000 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
pH: 9 - 11

Serious eye damage/irritation : Causes serious eye irritation.
pH: 9 - 11

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : None under normal use.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Gastrointestinal complaints. Nausea. Vomiting.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2,2'-iminodiethanol, diethanolamine	CAS No 111-42-2	1-5
-------------------------------------	-----------------	-----

IL Metal Working Lubricant/Coolant

Safety Data Sheet



California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.