



WHOOSH

DRY-FILM PTFE RESIN LUBRICANT

- EXCELLENT LUBRICITY
- LONG WEAR LIFE

DANGER:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

See back panel for further cautions and first aid instructions.

NET WEIGHT: 12.25 oz. (347 g)

WHOOSH offers excellent low friction, dry-film lubrication in an easy to use aerosol container. This fast drying lubricant adheres to many substrates including wood, metal, fabric, plastic and rubber. Typical applications include: window glides, tools, tumbler locks and assemblies, dry gear and chain lubricant, and hinges. **WHOOSH** also provides an excellent water and weather barrier.



DANGER:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not breathe gas, mist, spray, vapors. Avoid breathing gas, mist, spray, vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection.

RESPONSE:

IF ON SKIN: Wash with plenty of water
IF skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell. Take off contaminated clothing and wash before reuse.

STORAGE:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations.

INGREDIENTS/CAS#:

Toluene (108-88-3); 2-propanol (67-63-0); Carbon dioxide, liquefied, under pressure (124-38-9); Polytetrafluoroethylene (9002-84-0).

NFPA® RATINGS:

Health: 2; Flammability: 4; Reactivity: 0

DIRECTIONS:

Shake Well Before Using. Be sure surface is clean and dry before coating. To ensure even coating, spray about 8 to 10 inches from the surface. Four to six light passes should build-up the required coating thickness (0.3 to 0.5 mil dry). WHOOSH is ready to use when dry to the touch - about 5 minutes at room temperature. For use as a mold or form release, be sure to completely cover all surfaces with the lubricant.

NOTE: May harm painted, plastic or waxed surfaces. Always test in an inconspicuous area before use.

⚠ WARNING:

This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

Sold by:



8124.050915