

Automotive Repairs



Boat & Marine Repairs



Hydraulic Line Repairs



Pipe & Plumbing Repairs



Pool & Spa Repairs



Sprinkler System Repairs

SHARE

WATER ACTIVATED FIBERGLASS WRAP

REPAIRS

Copper • Rubber • Plastics • Fiberglass PVC Pipe • Galvanized • Concrete & More!

Danger:

May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction

Prevention:

Avoid breathing dust fune gas/ mist/vapours/spray. Contamination work clothing should hot be allowed outlof the workplade. Wear protective gloves.

Response:\

If INHALED Remove person to fresh air and keep comfortable on breathing. If experiencing siratory symptoms: Get emergency medical attention. F ON-SKIN: Wash with plenty of ater. If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse. DISPOSAL: Follow the waste disposal requirements of your

country, state, or local authorities Used material may be disposed of in municipal trash.

INGREDIENTS/CAS#

Polyisockanate Prepolymer (TS 44 Diphenylinethane Disocyanate (MDI) (101-68-8); Polymeric Dionenylmethane isbevanate (pMDI) (9016-87-9): Diphenylmethane Diisocyanate (MDI) Mixed Isomers (26447-40-5); Polyester Resin (TS): Zinc Sulfide (1314-98-3)

Directions inside package. NFPA® RATINGS:

Health: 1; Flammability: 0; Reactivity: 0

1793.021615

CUT HERE T(1 OPEN

- USE THIS KITON UP TO 1 INCH DIAMETER PIPE! 2" X 48" WRAP
- Works on Wet, Dry, Clean & Dirty Pipes!
- EPA APPROVED! ANSI/NSF 61 COMPONENTS.

Cures in 20 minutes



Apply Epoxy Putty



Immerse Wrap in Water



Wrap Pipe



Tighten for 4 minutes

AS STRONG AS STEEL