

POWDERED CAR WASH

Powdered Car, Truck & Trailer Wash

Form: Powder

Color: Blue

Odor: None

pH: N/A

Solubility (in water): Soluble
(in mineral spirits): No data available

VOC Content (% by weight): <0.5

Flash Point (ASTM D-7821): N/A

Specific Gravity: N/A

Density: N/A

Storage Stability (at 70°F): 1 year

Ingredients	C.A.S. #
Sodium Sulfate.....	7757-82-6
Sodium Carbonate.....	497-19-8
Sodium Tripolyphosphate	7758-29-4
Sodium Dodecylbenzenesulfonate .	25155-30-0
Water.....	7732-18-5

Other Uses...

- **Golf Cart Wash**
- **Hand Dish Wash Soap**
- **High Pressure Washer Soap**
- **Powdered Soak Tank Cleaner**
- **Transmission Wash**
- **Powdered Floor Cleaner**
- **Automatic Washers**

DIRECTIONS: For best results, wash vehicle in a protected or shady area, not in the hot sun. Use 2 to 6 ounces of POWDERED CAR WASH in one gallon of warm or hot water. Spray, mop or sponge solution onto wet vehicle and allow to act for several minutes. Rinse thoroughly with clean water. To avoid streaking, begin washing the lower soiled surfaces and move to the upper surfaces.

POWDERED CAR WASH may also be used in automatic washers. Use 1 to 3 ounces per gallon of water in the wash tank, or follow the instructions provided by the equipment manufacturer.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions	None