

OIL TYCOON

Liquid Stain Absorbent

Form: Liquid

Color: Opaque, off white

Odor: Mild

pH: 9.0 – 11.0

Solubility (in water): Soluble
(in mineral spirits): Insoluble

Flash Point (ASTM D-7821): None

VOC Content (% by wt): < 1.0

Specific Gravity: 1.04 g/cm³

Density: 8.93 lbs/gal

Storage Stability (at 70°F): 1 years

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
Surfactant Blend.....	Proprietary
d-Limonene	5989-27-5
Sodium Metasilicate.....	6834-92-0
Sodium Hydroxide	1310-73-2

Great for stains from...

- **Automotive fluids**
(Gas or Diesel, Oils, Brake, Hydraulic, Transmission, Power Steering)
- **Antifreeze**
- **Grease**
- **Silicone oil**
- **Barbecue grill stains**
- **Tar**
- **Tree sap**
- **Safe on asphalt, concrete, paving stones, pressure treated wood or composite decking**

DIRECTIONS: Pour, spray or brush OIL TYCOON onto stain so that the stain is completely covered. Deeper stains may require heavier or repeat application. Allow OIL TYCOON to completely dry, which may take up to 3 hours depending on ambient conditions. Simply sweep or rinse away OIL TYCOON and the stain.

HMIS®				NFPA	
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Physical Hazard	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions	None