



# ANTI-SEIZE



## High Temperature & Pressure Lubricant

PROTECTS AGAINST  
SEIZING • GALLING • CORROSION  
GALVANIC PITTING • RUST  
OF ALL THREADED PARTS

Net Weight: 12 Oz. (340 g)

### DANGER:

CONTENTS UNDER PRESSURE.

EXTREMELY FLAMMABLE AEROSOL. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SERIOUS EYE IRRITATION

SEE BACK PANEL FOR FURTHER CAUTIONS AND FIRST AID INSTRUCTIONS.

**KEEP OUT OF REACH OF CHILDREN**

**ANTI-SEIZE** is a high performance copper-based lubricant designed for use on all threaded fasteners, gaskets and hose connections. It prevents seizing and galling even under the most adverse conditions of pressure, moisture and heat up to 2,100°F.



#### DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation.

#### PREVENTION:

Keep away from heat/sparks/open flames/hot surfaces.  
- No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye/face protection.

#### RESPONSE:

**IF SWALLOWED:** Immediately call a poison center/doctor.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Do NOT induce vomiting. If eye irritation persists: Get medical advice/attention.

#### STORAGE:

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F.

#### DISPOSAL:

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### INGREDIENTS/CAS#:

Acetone (67-64-1); Butane (106-97-8); Copper (7440-50-8); Naphtha (petroleum), Light Alkylate (64741-66-8); Propane (74-98-6); Distillates (Petroleum), Hydrotreated Light (64742-47-8); Triethanolamine (102-71-6); Aluminum (7429-90-5)

#### NFPA® RATINGS:

Health: 2; Flammability: 3; Reactivity: 0

#### DIRECTIONS:

Surface must be free of dirt, grease and oil. Shake can until agitator ball begins to rattle freely for at least 30 seconds. In upright position, hold nozzle 8 to 10 inches from surface and apply by spraying ANTI-SEIZE in short bursts. After using, clean the spray nozzle by turning can upside down and spraying until only gas is expelled.

#### CAUTIONS:

Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN. **Warning:** This product contains a chemical(s) known to the state of California to cause cancer.

Sold by:

8221.021615

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • [www.sharecorp.com](http://www.sharecorp.com)