Safety Data Sheet



SECTION 1: Product and company identification

Product name : Essential Mist – Hill Side Fresh

Use of the substance/mixture : Aerosol

Odorant

Product code : 842701

Company : Share Corporation

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1 H222 Eye Irrit. 2A H319 STOT SE 3 H336

Full text of H statements: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





H603

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Causes serious eye irritation May cause drowsiness or dizziness

Precautionary statements (GHS-US) : Keep away from heat, sparks, open flames, hot surfaces. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Avoid breathing mist, vapors Wash thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear eye protection, face protection

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Call a POISON CENTER, a doctor if you feel unwell If eye irritation persists: Get medical advice/attention Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1 Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Date of issue: 10/12/2016 Revision date: 06/07/2016 Version: 1.1 P GHS SDS Page 1 of 7





| Name | Product identifier | % | GHS-US classification |
|----------------------------------|--------------------|---------|--|
| acetone, propan-2-one, propanone | (CAS No) 67-64-1 | 60 - 80 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| propane | (CAS No) 74-98-6 | 10 - 20 | Flam. Gas 1, H220 Compressed gas, H280 |
| butane | (CAS No) 106-97-8 | 10 - 20 | Flam. Gas 1, H220 Compressed gas, H280 |

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

If breathing is difficult, give oxygen. Get immediate medical attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. show this sheet where possible. Keep victim warm and rested.

First-aid measures after inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact

Wash with water and soap. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

Call a poison center or a doctor if you feel unwell. Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes serious eye irritation. May cause drowsiness or dizziness.

Symptoms/injuries after inhalation May cause drowsiness or dizziness.

Symptoms/injuries after skin contact

: Contact during a long period may cause light irritation.

Symptoms/injuries after eye contact

Causes serious eye irritation.

Symptoms/injuries after ingestion

Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Keep watching the victim. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. Dry powder. Carbon dioxide. Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Extremely flammable aerosol. Under fire conditions closed containers may rupture or explode.

Combustion produces irritating gases.

Explosion hazard

: Contents under pressure. Pressurized container: may burst if heated.

Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions

: Exercise caution when fighting any chemical fire. Move containers away from the fire area if this can be done without risk. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Stay upwind/keep distance from source. Evacuate unnecessary personnel. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

Protective equipment

: Do not enter without an appropriate protective equipment. Advice local authorities if considered necessary. DO NOT touch spilled material. Ventilate the area thoroughly, especially low lying areas

(basements, work pits etc.).

Emergency procedures : Do not breathe gas. Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area.

6.1.2. For emergency responders

6.1.1. For non-emergency personnel

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

Date of issue: 10/12/2016 Revision date: 06/07/2016 Version: 1.1 P GHS SDS Page 2 of 7

Safety Data Sheet



6.2. Environmental precautions

Avoid release to the environment. Advice local authorities if considered necessary. Stop leak if safe to do so. Do not contaminate water with the product or its container. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment

Eliminate every possible source of ignition. Prevent the product from entering drains or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Form with air vapors (heavier than air) who stay on the floor. Stop leak if safe to do so. Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid. Isolate area until gas has dispersed. Collect spillage.

Methods for cleaning up : Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Do not use if spray button is missing or defective. Pressurized container: Do not pierce or burn, even after use. Keep away from heat, sparks and flame.

Precautions for safe handling

: Avoid prolonged and repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Do not breathe gas/vapor/aerosol. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. . Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Ground/bond container and receiving equipment. Do not re-use empty containers. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Observe normal hygiene standards. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Do not discharge the waste into the drain. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Prevent the build-up of electrostatic charge.

: Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Hygiene measures

: Pressurized container. Do not puncture, incinerate or crush. Keep away from heat, hot surfaces,

sparks, open flames and other ignition sources. No smoking.

Storage conditions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures

exceeding 50 °C/ 122 °F. Refrigerate.

Storage temperature : < 49 °C Storage area : Aerosol 3.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| acetone, propan-2 | 2-one, propanone (67-64-1) | | |
|-------------------|----------------------------|--------------------------|--|
| ACGIH | ACGIH TWA (ppm) | 250 ppm | |
| ACGIH | ACGIH STEL (ppm) | 500 ppm | |
| ACGIH | Remark (ACGIH) | eye irr; CNS impair; BEI | |
| OSHA | OSHA PEL (TWA) (mg/m³) | 2400 mg/m³ | |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm | |
| propane (74-98-6) | | | |
| ACGIH | ACGIH TWA (ppm) | 1000 ppm | |
| OSHA | OSHA PEL (TWA) (mg/m³) | 1800 mg/m³ | |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm | |
| butane (106-97-8) | | | |
| ACGIH | ACGIH TWA (ppm) | 1000 ppm | |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm | |

Date of issue: 10/12/2016 Revision date: 06/07/2016 Version: 1.1 P GHS SDS Page 3 of 7

Safety Data Sheet

SHARE

8.2. Exposure controls

Appropriate engineering controls

Ensure good ventilation of the work station. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

Gloves. Protective goggles. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state · Gas : Aerosol. Appearance Odor : Pleasant scent Odor threshold No data available No data available pН No data available Melting point Freezing point No data available Boiling point 132.89 °F Estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : No data available **Explosion limits** No data available Explosive properties : No data available Oxidizing properties No data available Vapor pressure No data available Relative density : No data available Relative vapor density at 20 °C No data available Specific gravity / density : 0.148 g/ml Estimated Solubility No data available Loa Pow No data available Log Kow No data available Auto-ignition temperature No data available Decomposition temperature No data available No data available Viscosity Viscosity, kinematic No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Viscosity, dynamic

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point. Incompatible materials.

: No data available

10.5. Incompatible materials

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue: 10/12/2016 Revision date: 06/07/2016 Version: 1.1 P GHS SDS Page 4 of 7

Safety Data Sheet

SHARE

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

use.

Likely routes of exposure : Skin and eyes contact;Inhalation

SECTION 12: Ecological information

12.1. Toxicity

Class (DOT)

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contents under pressure. Do not puncture, incinerate or crush.

Waste disposal recommendations : Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas

2

Marine pollutant : Yes (IMDG only)



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82

Date of issue: 10/12/2016 Revision date: 06/07/2016 Version: 1.1 P GHS SDS Page 5 of 7

Safety Data Sheet

DOT Packaging Exceptions (49 CFR

173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

: 150 kg

: 306

: 75 kg

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : AEROSOLS

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : UN1950

Proper Shipping Name (IATA) : Aerosols, flammable
Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

| acetone, propan-2-one, propanone (67-64-1) | | | | |
|--|------------------------------------|--|--|--|
| Not listed on SARA Section 313 | (Specific toxic chemical listings) | | | |
| CERCLA RQ | 5000 lb | | | |
| propane (74-98-6) | | | | |
| Not listed on SARA Section 313 | (Specific toxic chemical listings) | | | |
| butane (106-97-8) | | | | |
| Not listed on SARA Section 313 | (Specific toxic chemical listings) | | | |
| | | | | |

California Proposition 65 - This product does not contain a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

| d of F-philases. | |
|------------------|--|
| H220 | Extremely flammable gas |
| H222 | Extremely flammable aerosol |
| H225 | Highly flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H319 | Causes serious eye irritation |
| H336 | May cause drowsiness or dizziness |

Date of issue: 10/12/2016 Revision date: 06/07/2016 Version: 1.1 P GHS SDS Page 6 of 7

Safety Data Sheet


NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury

unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 10/12/2016
 Revision date: 06/07/2016
 Version: 1.1
 P GHS SDS
 Page 7 of 7