



# Please Release Me

## ASPHALT RELEASE AGENT

### DANGER

May be corrosive to metals. Causes skin irritation.  
Causes serious eye damage. Suspected of causing cancer.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)**

# Please Release Me



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**



### DANGER:

May be corrosive to metals. Causes skin irritation.  
Causes serious eye damage. Suspected of causing cancer.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves

**IF ON SKIN:** Wash with plenty of soap and water.

**If skin irritation occurs:** Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

**If exposed or concerned:** Get medical advice/attention.

Absorb spillage to prevent material damage.

Store locked up. Store in corrosive resistant container with a resistant inner liner.

### DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations.

### NFPA® RATINGS:

Health: 2; Flammability: 1; Reactivity: 0

### CONTAINS/CAS#:

Water (7732-18-5); Distilled Tall Oil (8002-26-4); Tetrasodium Ethylenediamine Tetraacetate (64-02-8); Potassium Hydroxide (1310-58-3); Methyl Ester, Soybean Oil (67784-80-9).

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

# Please Release Me

**PLEASE RELEASE ME** is an asphalt release that encapsulates dump beds, rollers, tools and equipment with a molecular film that prevents sticking and adhesion of asphalt.

**USES:** Developed as an effective alternative to diesel fuel, now banned for this use by the E.P.A. Provides a thin uniform emulsion that acts like millions of ball bearings between equipment surface and the hot sticky asphalt. May be sprayed to form a heat-resistant shield that will not run off, reducing the chance of soil contamination.

**SNOW:** The product's molecular film also encapsulates snow plows and dump beds to prevent snow from sticking and causing expensive down time.

**APPLICATION 1:** May be applied manually by mixing one quart of product with 2 to 2-1/2 gallons of water and applying with a 3 gallon sprayer. Must agitate briskly to ensure good mixture.

**APPLICATION 2:** For large volume usage, use with a proportioning device diluting one part release agent with 20 parts of water.



**WARNING:** This product can expose you to Formaldehyde, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

0700.021218



Please Recycle.