



Belt Dressing

Drive Belt Reconditioner

**INCREASES POWER AND PERFORMANCE
BY REDUCING SLIPPAGE ON RUBBER,
LEATHER, FABRIC OR CANVAS BELTS**

Net Weight: 12 ounces (340 grams)

DANGER:

Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated.

KEEP OUT OF REACH OF CHILDREN

See cautions on back panel.

BELT DRESSING rejuvenates and protects all types of vehicle fan and drive belts, "V" belts, and industrial power transfer belts made from rubber, canvas, fabric or leather. Treated drive belts last longer and have less slip. BELT DRESSING will not crack, glaze or collect dirt or dust and it also improves performance in wet environments. Use on all belts found on meat processing equipment such as slicers, grinders and sealers. Works on all industrial and farm belt-driven equipment, auto fan and water pump belting, power tool belting and other belt driven equipment.



DANGER:

Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and eye irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

PREVENTION:

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves.

RESPONSE:

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting.

STORAGE:

Store locked up.

DISPOSAL:

Dispose of contents and container in accordance with local, state, and national regulations.

INGREDIENTS/CAS#:

Aliphatic distillate (64742-89-8); Propane/n-Butane (68476-86-8); Resin Ester (N/A)

NFPA® RATINGS:

Health: 1; Flammability: 3; Reactivity: 0

DIRECTIONS:

With belt running, hold can 12-16 inches from surface and spray back and forth on inner surface of belt. When applying to "V" belts, the spray may be applied to the sheaves or directly onto the belt. Spray small amounts at a time until inner working surface of belt is completely covered. Apply sparingly, do not saturate belt. Stay clear of moving belts. Injury may occur.

Sold by:

8206.030315

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com