

BRUSH TOP ANTI-SEIZE

High Temperature & Pressure Grease

Form: Silver gray paste

Color: Silver

Odor: Odorless

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): 0%

Flash Point (ASTM D-7821): None

Specific Gravity: 1.02 g/cm³

Density: 8.51 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S.

Naphthenic Petroleum Distillate...64742-53-6
Hydrotreated Naphthenic Petroleum Distillate
.....64742-52-5
Aluminum.....7429-90-5
Graphite.....7782-42-5
Fumed Silica.....112945-52-5

Great for use by...

- Municipalities
- Refineries
- Shipyards
- Factories
- Mining Operations
- Power generating plants
- Chemical plants
- Industrial plants
- Factories
- Steel mills

Provides Protection For...

- Pipe threads
- Gaskets
- Motors
- Engines
- Bearings
- Gears
- Boilers
- Turbines
- Oil and ore drills
- Exhaust systems
- Heat exchangers
- Torque tools

DIRECTIONS: This product is a grease in a screw top can with brush top applicator. Use brush to apply a thin, even coat to desired part.

HMIS			NFPA		
	Severe	4	Extreme		
Health.....1	Serious	3	High	Health.....1	
Flammability.....0	Moderate	2	Moderate	Flammability.....0	
Reactivity.....1	Slight	1	Slight	Reactivity.....1	
Personal Protection.....X	Minimal	0	Insignificant	Special Precautions.....None	