

PROTECTS UP TO 11 CU. FT.

10 Emitters/Carton

Plastic cartridge filled with VpCI* (Vapor phase Corrosion Inhibitors and leaked with Tyvek* breathable membrane. Remove plastic cartridge from cellophage package.

Remove adhesive backing. Place emitter using the pressure-sensitive tape on clean dry surface.

Record date emitter was installed. Service life up to two years under typical conditions or until

color changes from off-white to black.

WARNING: Harmful if swallowed. Causes skin irritation.
Causes serious eye irritation. May cause respiratory urritation.
PREVENTION: Avoid breathing dust/fume/gas/mist/2000usc

spray. Wear protective gloves/protective clothing/eye prot

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to be continue insing Specific treatment (see on this label).

Store locked up. Dispose of contents/container in accordance with local/regional/national/pernational regulations.

NFPA® RATINGS: Health: 2; Flar mability: 1; Reactivity: 0 INGREDIENTS/CAS#: Proprietary (b/A); Benzotriazole (95-14-7)

1905.051515

FOR CHEMICAL EMERGENCY: SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 800-424-9300

MADE IN THE U.S.A.



Share Corp. • 2.0. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com