



four way ACTION

PENETRANT & RUST PREVENTATIVE

- Quickly Penetrates Rust
- Displaces Moisture
- Lubricates and Prevents Corrosion
- Non-Flammable
- Non-Conductive, High Dielectric Strength: 39,500V

DANGER

Keep out of reach of children. Read label and SDS before use. Contains gas under pressure; may explode if heated. May cause cancer; suspected of causing genetic defects (route of exposure: inhalation) May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

KEEP OUT OF REACH OF CHILDREN

See side panel for additional precautions.

Net Wt. 17 oz. (482 g)

FOUR WAY ACTION frees rusted and corroded screws, nuts, and bolts as well as aluminum and copper fittings. Use it to displace moisture on electronic and electrical equipment, protect metal, lubricate precision instruments and waterproof ignition systems and terminals. **FOUR WAY ACTION** saves production and repair costs as it protects and preserves equipment from failures due to moisture.



DANGER:

Keep out of reach of children. Read label and SDS before use. Contains gas under pressure; may explode if heated. May cause cancer; suspected of causing genetic defects (route of exposure: inhalation) May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapors or spray. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use. Wash hands and face thoroughly after handling. Wear protective gloves, clothing, and eye protection. Do not eat, drink or smoke when using this product. Contaminated clothing must not be allowed out of the workplace.

RESPONSE:

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs:

Get medical attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists:

Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

If exposed or concerned: Get medical attention.

STORAGE:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up.

DISPOSAL:

Dispose of contents and container in accordance with all local, regional, and national regulations.

DIRECTIONS:

SHAKE WELL BEFORE USING. Hold nozzle 6 to 8 inches from surface to be treated. Saturate area with **FOUR WAY ACTION**. Severely corroded parts may need additional treatment.

INGREDIENTS/CAS#:

Trichloroethylene (79-01-6); Distillates (petroleum), hydrotreated light (64742-47-8); Hydrotreated Heavy Naphthenic Distillate (64742-52-5); Carbon Dioxide (124-38-9)

NFPA® RATINGS:

Health: 2; Flammability: 1; Reactivity: 0



Please Recycle.

Sold by:



8097.081915

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com