



P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com

HI TEMP RED GREASE is a multi-purpose, non-melt extreme pressure grease. The additives in this grease give resistance to shock and impact, do not liquefy at high temperatures like soap based greases and remain pumpable at low temperatures.

Great for use in:


- Marine applications
- Agricultural applications
- Automotive applications
- Industrial applications

Provides Protection for:

- Couplings
- Pumps
- Ball joints
- Fifth wheels
- Universal joints
- Ball bearings
- Roller bearings
- Mechanical linkages

Properties:

TYPICAL SPECIFICATIONS	
Product Number.....	184901
Appearance.....	Tacky semi-solid
Texture.....	Smooth
Color.....	Red
Fragrance.....	Mild petroleum
NLGI Grade.....	#2 and harder
Flash Point, °F.....	N/A
Viscosity @ 100 °F, SUS.....	2600
Viscosity @ 210 °F, SUS.....	150
Worked Penetration, 77 °F (25 °C).....	250 - 280
Dropping Point, °F (°C), ASTM D 2265.....	None
Temperature Range, °F.....	0 - 450
Timken OK Load D 2509, lbs.....	50
4-Ball EP, ASTM D 2596, Weld Load, kg.....	250
Thickener Type.....	Bentone



Hi Temp Red Grease

Multi-Service High Temperature Grease

NET WT. 14 OZ.