

# HI TEMP RED GREASE

## Multi-Service High Temperature Grease

**Form:** Semi-Solid

**Color:** Red

**Odor:** Slight Petroleum

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Soluble

**Flash Point (°F):** N/A

**Specific Gravity:** 7.46 lbs/gal

**Density:** 0.894 g/cm<sup>3</sup>

**Storage Stability (at 70°F):** 1 year

### Great for use in...

- **Marine Applications**
- **Agricultural Applications**
- **Steel Foundries**
- **Automotive Applications**
- **Industrial Applications**
- **Stone Quarries**
- **Boiler Operations**
- **Oil Fields**
- **Hot Strip Mills**
- **Cement Plants**
- **Air Conditioners**
- **Wheel Bearings**

### TYPICAL SPECIFICATIONS

NLGI Grade .....	2 and Harder
Color .....	Red
Thickener Type .....	Inorganic
Viscosity @ 100°F (38°C), SUS .....	2600
Viscosity @ 210°F (99°C), SUS .....	150
Viscosity Index.....	95
Worked Penetration, 77°F (25°C) .....	250-280
Dropping Point ASTM D 2265 .....	None
Timken OK Load ASTM D 2509, lbs.....	50
4-Ball EP, ASTM D 2596, Weld Load, kg .....	250
Temperature Range, °F .....	0-450
Rust Prevention, ASTM D 1743 .....	Pass

HMIS®			NFPA		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	1
Physical Hazard .....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions .....	None