

# CEILING TILE WHITENER

## Colonial White Acoustical Tile Rejuvenator

**Form:** Aerosol Liquid

**Color:** White/Off White

**Odor:** Solvent

**pH:** N/A

**Solubility (in water):** N/D  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** 53.7

**Flash Point (ASTM D-7821):** - 2°F

**Specific Gravity:** 0.77 – 0.90 ± 0.01 g/cm<sup>3</sup>

**Density:** 6.43 – 7.51 ± 0.05 lbs/gal

**Storage Stability (at 70°F):** 1 year

### Ingredients

### C.A.S. #

Propane .....	74-98-6
Toluene .....	108-88-3
n-Butane.....	106-97-8
Calcium Carbonate.....	1317-65-3
VM&P Naphtha .....	64742-89-8

### Use it to cover...

- **Water Spots**
- **Stains**
- **Blackening around air conditioning ducts**
- **Any Acoustical Tile Discoloration**

**DIRECTIONS:** Shake can vigorously for one minute after mixing ball is heard, and occasionally during use. For best results, can should be at room temperature, 70° to 90° F (21° to 32° C). Before spraying, be sure to cover floor, furniture and ceiling fixtures to prevent spotting. If the ceiling stain is near a wall, be sure to cover the nearby wall area. Hold can upright approximately 8 to 10 inches from tile and press the sprayhead to the side. Cover stain thoroughly. To prevent clogging and to clean the sprayhead for future use, turn the can upside down and spray for about 2 seconds, or until no more paint comes out of can.

HMIS			NFPA		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	3
Reactivity.....	Slight	1	Slight	Reactivity.....	3
Personal Protection .....	Minimal	0	Insignificant	Special Precautions .....	None