

INSTANT LUBRICATION
FAST DRYING

WITHSTANDS
HIGH TEMPERATURE
AND EXTREME PRESSURE

Net Weight: 10.25 ounces

DANGER:

EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. See back panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

VOC Compliant

MOLY LUBE provides instant lubrication under extreme conditions. It quickly dries to a hard, black coating of molybdenum disulfide and adheres to most substrates, especially metal, with minimal surface preparation. MOLY LUBE resists wear and abrasion under extreme pressures and temperatures. Unlike many other lubricants, the MOLY LUBE lubricating film dries completely and will not attract dirt or dust. Ideal for chain lubrication, maintenance on furnaces, kilns, ovens, conveyors, gaskets, anti-seize and mold release applications.

DIRECTIONS

SHAKE WELL BEFORE USING. For best results apply to a dry, clean surface at room temperature. Shake until agitator ball rattles, then for 30 seconds more. Hold can 6 to 8 inches from surface and spray a thin, even film. Avoid spraying too thick, as this will decrease the effectiveness. Clean nozzle after each use by inverting can and pressing valve for 2 to 3 seconds.

DANGER:

EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. SKIN, EYE and RESPIRATORY TRACT IRRITANT.

PRECAUTIONS: Keep away from heat, sparks, and open flame. Do not smoke, extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Use with adequate ventilation. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 °F. Keep out of the reach of children. Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal. See MSDS for additional information.

FIRST AID:

If In Eyes: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

If On Skin: Wash with soap and water. If irritation persists, obtain medical attention.

If Swallowed: If swallowed, do NOT induce vomiting. Call physician immediately. Never give anything by mouth to an unconscious person.

If Inhaled: Remove person to fresh air. Administer artificial respiration if breathing has stopped.

KEEP OUT OF REACH OF CHILDREN

Health 2
Flammability 4
Reactivity 0

| HMIS | | NFP |
|----------|---|-------------|
| Severe | 4 | Extrem |
| Serious | 3 | Hig |
| Moderate | 2 | Modera |
| Slight | 1 | Slig |
| Minimal | 0 | Insignifica |



| This Product Contains | CAS Number |
|----------------------------|------------|
| Propane/Isobutane/n-Butane | 68476-86-8 |
| 2-Propanol | 67-64-1 |
| Toluene | 108-88-3 |
| Isopropyl alcohol | 67-63-0 |
| Molybdenum disulfide | 1317-33-5 |

8225•061510

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com