**QuestSpecialty** 



## **Premium Lithium E.P. Grease**



## **Premium Lithium** E.P. Grease

Premium Grasa Litio E.P.

Resists Thinning or Hardening in Medium Sized High Speed Bearings

Lithium Grease with Oxidation Inhibitors & Extreme Pressure Additives for a Wide Range of Uses

Protects Surfaces Against Corrosion

Operating Range of 0°F to 350°F

**CAUTION/PRECAUCIÓN:** KEEP OUT OF REACH OF CHILDREN SEE ADDITIONAL CAUTIONS ON BACK PANEL NO SE DEJE AL ALCANCE DE LOS NIÑOS

VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO NET CONTENTS: 14 OZ. (397 g)

> QuestSpecialty Corporation PO Box 624 • Brenham, TX 77834 • 713.896.8188

industrial and agricultural ap- 8 ounces contact physician. plications. Does not dry out after use as some clay based PRECAUCIÓN: No se deie al sized high speed bearings.

ages, pumps, universal joints, de 8 onzas contacte al médico. ball joints, fifth wheels, wheel bearings, chassis.

possible. For ball type grease fit- 7065 OPC (N/A). tings: Fill until old grease comes out. Clean exposed areas with NLGI GRADE: 2 degreaser to remove old grease. Pump in new grease.

MODO DE EMPLEO: Invecte gra- sonal - A. sa nueva hasta que la grasa vieja salga. Remueva la grasa vieja si Made in USA es posible. Para conexiones de tipo bola: Llene hasta que la grasa vieia salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieia. Inyecte nueva grasa.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eve contact, flush with water, see physician if oily film persists.

A multi-use grease for hun- For skin, wash with soap and dreds of automotive, marine, water. For ingestion of more than

greases do. Remains pumpable alcance de los niños. Puede at low temperatures. Forms causar irritación a los ojos. El protective film, resisting rust contacto prolongado puede and corrosion. Resists chemical causar irritación de la piel. Si es breakdown and oxidation. This ingerido, puede causar náusea. waterproof Jubricant will not vomito v diarrea. Si hav contacto wash out. Suitable for medium con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hav contac-USES: Ball bearings, roller bear- to con la piel, lave con agua v ings, couplings, mechanical link- jabón. Para la ingestión de más

CONTAINS (CAS#): Naphthenic Oil (64742-52-5). Lithium 12-**DIRECTIONS FOR USE:** Pump hydroxystearate (7620-77-1). in new grease until old grease Lithium stearate (4485-12-5). comes out. Remove old grease if Elco 102 (68649-42-3). Lubrizol

HMIS Ratings: Health - 1. Flammability - 1, Reactivity - 0, Per-

600005052

