Safety Data Sheet



SECTION 1: Product and company identification

Product name : Handful Sanitizer

Use of the substance/mixture : Aerosol

Hand sanitizers

Product code : 820301

Company : Share Corporation

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Compressed gas H280 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

Signal word (GHS-US)

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04



GHS02

: Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Causes serious eye irritation

Precautionary statements (GHS-US) : Keep away from heat, hot surfaces, open flames, sparks. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Wash thoroughly after handling

Wear eye protection

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention Protect from sunlight. Store in a well-ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

5.2. WHALUIE			
Name	Product identifier	%	Classification (GHS-US)
ethanol	(CAS No) 64-17-5	60 - 65	Flam. Liq. 2, H225 STOT SE 3, H336
butane	(CAS No) 106-97-8	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
propane	(CAS No) 74-98-6	1 - 5	Flam. Gas 1, H220 Compressed gas, H280

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

Date of issue: 9/15/2015 Revision date: 05/28/2015 Version: 1.0 P GHS SDS Page 1 of 6

Safety Data Sheet

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact : Rinse with water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : May be harmful if swallowed. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes serious eye irritation. Extremely flammable. Contents under pressure.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.
Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Under fire conditions closed containers may rupture or explode.

Explosion hazard : Bursting aerosol containers may be propelled from a fire at high speed. Contains gas under

pressure; may explode if heated. Vapors may travel long distances along ground before

igniting/flashing back to vapor source.

Reactivity : On heating/burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon

dioxide.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Evacuate area. No action shall be taken involving

any personal risk or without suitable training. Move containers away from the fire area if this can be

done without risk. Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No flames, No sparks. Eliminate all sources of ignition. Evacuate area.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area. Stop release. Stop leak if safe to do so.

6.2. Environmental precautions

Absorb and/or contain spill with inert material, then place in suitable container. Isolate hazard area. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Eliminate every possible source of ignition. Use water spray to disperse

the vapors. Prevent the product from entering drains or confined areas.

Methods for cleaning up : Take up liquid spill into inert absorbent material. This material and its container must be disposed of

in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not puncture, incinerate or crush. Store in dry, cool area.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Intentional misuse by deliberately concentrating and

inhaling may be harmful or fatal. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container.

Date of issue: 9/15/2015 Revision date: 05/28/2015 Version: 1.0 P GHS SDS Page 2 of 6

Safety Data Sheet

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

Store in a dry place. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Incompatible products : acids. Strong oxidizing agents.

Incompatible materials : Heat sources. Open flame. Sources of ignition.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
ACGIH	ACGIH STEL (ppm)	1000 ppm	
ethanol (64-17-5)			
ACGIH	ACGIH STEL (ppm)	1000 ppm	
ACGIH	Remark (ACGIH)	URT irr	
propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Protective clothing. Safety glasses. Use appropriate personal protective equipment when

risk assessment indicates this is necessary.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : White. Foam.

Odor : Pleasant odor

Odor threshold : No data available

pH : 7 - 8

Melting point No data available Freezing point No data available Boiling point : No data available Flash point 70 °F (liquid portion) Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) No data available : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure Relative density No data available Relative vapor density at 20 °C No data available

Specific gravity / density : 0.8 g/ml

Solubility : Soluble in water.
Log Pow : No data available
Log Kow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available

Date of issue: 9/15/2015 Revision date: 05/28/2015 Version: 1.0 P GHS SDS Page 3 of 6

Safety Data Sheet

Viscosity, dynamic : No data available

VOC content : 67 %

SECTION 10: Stability and reactivity

10.1. Reactivity

On heating/burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Welding.

10.5. Incompatible materials

acids. Oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
ATE CLP (oral)	10740.000 mg/kg body weight

Skin corrosion/irritation : Not classified

pH: 7 - 8

Serious eye damage/irritation : Causes serious eye irritation.

pH: 7 - 8

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified.
Specific target organ toxicity (repeated : Not classified

exposure)

. Hot oldoomod

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms/injuries after ingestion : May be harmful if swallowed.

Likely routes of exposure : Dermal;Inhalation

SECTION 12: Ecological information

12.1. Toxicity

ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	9300 mg/l (48 h; Daphnia magna)
LC50 fish 2	13000 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)
Threshold limit other aquatic organisms 1	65 mg/l (72 h; Protozoa)
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa; Growth rate)
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda; Growth rate)

12.2. Persistence and degradability

 Date of issue: 9/15/2015
 Revision date: 05/28/2015
 Version: 1.0
 P GHS SDS
 Page 4 of 6

Safety Data Sheet



ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O /g substance
Chemical oxygen demand (COD)	1.70 g O /g substance
ThOD	2.10 g O /g substance
BOD (% of ThOD)	0.43 % ThOD

12.3. Bioaccumulative potential

ethanol (64-17-5)	
BCF fish 1	1 (72 h; Cyprinus carpio)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport hazard class(es) (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



: 75 kg

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306 173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft : 150 kg

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Date of issue: 9/15/2015 Revision date: 05/28/2015 Version: 1.0 P GHS SDS Page 5 of 6

Safety Data Sheet



butane (106-97-8)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
propane (74-98-6)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	

California Proposition 65 - This product does not contain trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

This product is covered under 21 CFR and is subject to certain labeling requirements. These requirements may differ from the classification criteria and hazard information required for safety data sheets and for workplace labels.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:


F	
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 9/15/2015
 Revision date: 05/28/2015
 Version: 1.0
 P GHS SDS
 Page 6 of 6