



CEILING TILE PAINT FOR
TEXTURED AND ACOUSTICAL CEILINGS
Covers Discoloration, Stains and Water Spots

V.O.C. Compliant

NET WEIGHT: 16.0 ounces (454 grams)

WARNING: FLAMMABLE LIQUID AND VAPOR. VAPOR
MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.
See back panel for further precautions and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

Use CEILING TILE WHITENER to cover water spots, stains and blackening around air conditioner vents. Primer is not required. It dries instantly to a unique micro-void finish to maintain acoustic properties. It will not harm tiles or cause them to sag or warp. Easy to use, because the vertical tip allows it to be sprayed straight up.

DIRECTIONS

Shake can vigorously for one minute after the mixing ball is heard, and occasionally during use. For best results, can should be at room temperature, 70° to 90°F (21° to 32°C). Before spraying, be sure to cover floor, furniture and ceiling fixtures to prevent spotting. If the ceiling stain is near a wall, be sure to cover the nearby wall area. Hold can upright approximately 8 to 10 inches from tile and press the sprayhead to the side. Cover stain thoroughly. To prevent clogging and to clean the sprayhead for future use, turn the can upside down and spray for about 2 seconds, or until no more paint comes out of can.

WARNING: FLAMMABLE LIQUID AND VAPOR.

VAPORS MAY CAUSE FLASH FIRE. Vapors may ignite explosively. Keep away from heat, sparks and open flame. Do not smoke during use. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Avoid contact with eyes, skin and clothing. Close container after each use.

WARNING: This product contains an ingredient known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID:

If In Eyes: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

If On Skin: Remove contaminated clothing and launder before reuse. Wash with soap and water. If irritation persists, obtain medical attention.

If Swallowed: Contact physician or poison control center immediately.

If Inhaled: Remove person to fresh air. If breathing has stopped, administer artificial respiration. If breathing is difficult, administer oxygen. Obtain medical attention.

KEEP OUT OF REACH OF CHILDREN

8016.100505

Health		HMIS		NFPA	
Severe	4	Severe	4	Extreme	3
Serious	3	Serious	3	High	3
Moderate	2	Moderate	2	Moderate	1
Slight	1	Slight	1	Slight	3
Minimal	0	Minimal	0	Insignificant	

This Product Contains

Propane.....	74-98-6
Toluene.....	108-88-3
n-Butane.....	106-97-8
Calcium Carbonate.....	1317-65-3
VM&P Naphtha.....	64742-89-8

CAS Number