Safety Data Sheet



SECTION 1: Product and company identification

Product name : Windshield Deicer

Use of the substance/mixture : Aerosol

Ice melter

Product code : 820901

Company : Share Corporation P.O. Box 245013

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Compressed gas H280
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation: gas) H331
STOT SE 1 H370
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Contains gas under pressure; may explode if heated Toxic if swallowed, in contact with skin or if inhaled

Causes damage to organs (optic nerve, central nervous system, Can cause blindness.)

Precautionary statements (GHS-US)

: Keep away from heat, sparks, open flames, hot surfaces, Do not smoke. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Do not breathe fume, mist, spray, vapors Avoid breathing fume, mist, spray, vapors

Wash thoroughly after handling

Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area

Wear protective gloves, protective clothing, eye protection

If swallowed: Immediately call a POISON CENTER, a doctor, Do NOT induce vomiting If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water If inhaled: Remove person to fresh air and keep comfortable for breathing

If exposed: Call a poison center/doctor Call a doctor, a POISON CENTER

Call a POISON CENTER, a doctor if you feel unwell Specific treatment (see First aid measures on this label)

Rinse mouth

Take off immediately all contaminated clothing Wash contaminated clothing before reuse

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Store in a well-ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Date of issue: 8/19/2015 Revision date: 05/07/2015 Version: 1.0 P GHS SDS Page 1 of 6

Safety Data Sheet



SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
methanol	(CAS No) 67-56-1	95 - 99	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
carbon dioxide, liquefied, under pressure	(CAS No) 124-38-9	1 - 5	Not classified

SECTION 4: First aid measures

4.	[.]	Descrip	otion of	first	aid	measure	25
----	-------------	---------	----------	-------	-----	---------	----

First-aid measures general

: If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or

doctor/physician if you feel unwell.

First-aid measures after skin contact

: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Take on contaminated clothing and wash it before reuse.

First-aid measures after eye contact

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Vomiting: prevent asphyxia/aspiration pneumonia.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Extremely flammable. Contents under pressure. Depression of the central nervous system. May be fatal if swallowed and enters airways. Causes damage to organs (central nervous system, eyes). Toxic if swallowed, in contact with skin or if inhaled.

Symptoms/injuries after inhalation

 Central nervous system depression. Repeated exposure by inhalation or skin absorption may cause systemic poisoning, brain disorders, and blindness. Toxic if inhaled. May cause drowsiness or dizziness. Headache.

Symptoms/injuries after skin contact

Toxic in contact with skin. May cause moderate irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/injuries after eye contact

: May cause severe irritation.

Symptoms/injuries after ingestion

May be fatal if swallowed and enters airways. MAY BE FATAL IF SWALLOWED. May be harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Flammable aerosol. Under fire conditions closed containers may rupture or explode.

Explosion hazard

: Vapors may travel long distances along ground before igniting/flashing back to vapor source. Contains gas under pressure; may explode if heated. Bursting aerosol containers may be propelled from a fire at high speed.

: Upon combustion: CO and CO2 are formed.

Reactivity

5.3. Advice for firefighters Firefighting instructions

: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed

containers.

Protection during firefighting

: Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Gas is denser than air. May accumulate in low areas e.g. close to the ground.

6.1.1. For non-emergency personnel

Protective equipment

: Do not enter without an appropriate protective equipment.

Date of issue: 8/19/2015 Revision date: 05/07/2015 Version: 1.0 P GHS SDS Page 2 of 6

Safety Data Sheet

Emergency procedures : Evacuate unnecessary personnel. NO open flames, NO sparks, and NO smoking.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Isolate area until gas has dispersed. Eliminate every possible source of

ignition. Use water spray to disperse the vapors. Collect spillage.

Methods for cleaning up : Take up liquid spill into inert absorbent material.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after

use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F.

Incompatible products : Strong oxidizing agents. acids.

Incompatible materials : Sources of ignition. Heat sources. Open flame.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.

Storage area : Store in a cool area. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1))		
ACGIH	ACGIH TWA (ppm)	200 ppm	
ACGIH	ACGIH STEL (ppm)	250 ppm	
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea	
carbon dioxide, lic	quefied, under pressure (124-38-9)		
ACGIH	ACGIH TWA (ppm)	5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)	
ACGIH	ACGIH STEL (ppm)	30000 ppm (Carbon dioxide; USA; Short time value; TLV - Adopted Value)	

8.2. Exposure controls

Personal protective equipment

: Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Protective goggles. Safety glasses.





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. clear. Liquid.
Odor : Solvent-like odor
Odor threshold : No data available

pH : 7 - 9

Melting point : No data available Freezing point : No data available

Date of issue: 8/19/2015 Revision date: 05/07/2015 Version: 1.0 P GHS SDS Page 3 of 6



Safety Data Sheet

SHARE

Boiling point 149 °F Methanol Flash point : < 50 °F (liquid portion) Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available Explosive properties No data available : No data available Oxidizing properties Vapor pressure No data available : No data available Relative density Relative vapor density at 20 °C : No data available

Specific gravity / density : 0.9 g/ml

Solubility Soluble in water. Log Pow No data available Log Kow : No data available Auto-ignition temperature : No data available Decomposition temperature No data available Viscosity : No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic

VOC content : 65 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. No flames, No sparks. Eliminate all sources of ignition. Welding. Open flame.

10.5. Incompatible materials

Oxidizing agent. acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: gas: Toxic if inhaled.

methanol (67-56-1)	
LD50 dermal rabbit	12800 mg/kg
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (gases)	64000.000 ppmV/4h
ATE CLP (dust, mist)	0.500 mg/l/4h

Skin corrosion/irritation : Not classified

pH: 7 - 9

Serious eye damage/irritation : Not classified

pH: 7 - 9

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs (optic nerve, central nervous system, Can cause blindness.).

Date of issue: 8/19/2015 Revision date: 05/07/2015 Version: 1.0 P GHS SDS Page 4 of 6

Safety Data Sheet

Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Central nervous system depression. Repeated exposure by inhalation or skin absorption may

cause systemic poisoning, brain disorders, and blindness. Toxic if inhaled. May cause

drowsiness or dizziness. Headache.

Symptoms/injuries after skin contact Toxic in contact with skin. May cause moderate irritation. Repeated exposure may cause skin

dryness or cracking.

Symptoms/injuries after eye contact : May cause severe irritation.

Symptoms/injuries after ingestion May be fatal if swallowed and enters airways. MAY BE FATAL IF SWALLOWED. May be

harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular

toxicity ranging from diminished visual capacity to complete blindness, and death.

: Dermal;Inhalation Likely routes of exposure

SECTION 12: Ecological information

12.1. Toxicity

carbon dioxide, liquefied, under pressure (124-3	8-9)
LC50 fish 1 35 mg/l (LC50; 96 h; Salmo gairdneri)	

12.2. Persistence and degradability

carbon dioxide, liquefied, under pressure (124-38-9)		
Persistence and degradability Biodegradability: not applicable. Not applicable (gas).		
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	

12.3. Bioaccumulative potential

carbon dioxide, liquefied, under pressure (124-38-9)	
Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport hazard class(es) (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols

> flammable, (each not exceeding 1 L capacity) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



: 150 kg

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

DOT Quantity Limitations Passenger : 75 kg

aircraft/rail (49 CFR 173.27)

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

DOT Quantity Limitations Cargo aircraft

Date of issue: 8/19/2015 Revision date: 05/07/2015 P GHS SDS Version: 1.0 Page 5 of 6

Safety Data Sheet



DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

methanol	CAS No 67-56-1	95 - 99
methanol (67-56-1)		
Listed on SARA Section 313 (Specific toxic chem	ical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb	

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3	
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3	
Compressed gas	Gases under pressure Compressed gas	
Flam. Aerosol 1	Flammable aerosol Category 1	
Flam. Liq. 2	Flammable liquids Category 2	
STOT SE 1	Specific target organ toxicity (single exposure) Category 1	
H222	Extremely flammable aerosol	
H225	Highly flammable liquid and vapor	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H331	Toxic if inhaled	
H370	Causes damage to organs	


NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical

attention was given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Date of issue: 8/19/2015 Revision date: 05/07/2015 Version: 1.0 P GHS SDS Page 6 of 6