Juicy Mango Air Freshener
Safety Data Sheet

SECTION 1: Product and company identification

Product name	:	Juicy Mango Air Freshener
Use of the substance/mixture	:	Aerosol Deodorant
Product code	:	8593
Company	:	Share Corporation P.O. Box 245013 Milwaukee, 53224 T 800-776-7192
Emergency number	:	Chemtrec: 800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 2 H223
Press. Gas (Comp.) H280

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :

GHS02 GHS04

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : Flammable aerosol
Contains gas under pressure; may explode if heated

Precautionary statements (GHS-US) : Keep away from heat, hot surfaces, open flames, sparks. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Petroleum gases, liquefied, sweetened, Petroleum gas, [A complex combination of hydrocarbons obtained by subjecting liquefied petroleum gas mix to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).]	(CAS-No.) 68476-86-8	10 - 30	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Muta. 1B, H340 Carc. 1A, H350

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove the victim into fresh air. Artificial respiration and/or oxygen if necessary. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth with water. Do not induce vomiting without medical advice. Drink plenty of water. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder. Carbon dioxide. Foam. Water spray. Water fog.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Contains gas under pressure; may explode if heated.

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not breathe fumes from fires or vapors from decomposition. Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No flames, no sparks. Eliminate all sources of ignition. No open flames. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

Emergency procedures : No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Take up liquid spill into inert absorbent material. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Collect spillage.

Methods for cleaning up : Take up liquid spill into inert absorbent material.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep cool. Protect from sunlight. Store in a well-ventilated place. Store in a dry place.

Incompatible products : alkalis. Strong oxidizers. Acids.

Storage area : Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum gases, liquefied, sweetened, Petroleum gas, [A complex combination of hydrocarbons obtained by subjecting liquefied petroleum gas mix to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] (68476-86-8)
Not applicable

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Safety glasses. Gloves. Use appropriate personal protective equipment when risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Gas
Appearance	:	Aerosol. White. mist.
Odor	:	characteristic
Odor threshold	:	No data available
pH	:	7
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	> 200 °F
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Specific gravity / density	:	0.97 g/ml
Solubility	:	Moderately soluble in water.
Log Pow	:	No data available
Log Kow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
VOC content	:	25 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent. Acids. alkalis.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	:	Not classified
Skin corrosion/irritation	:	Not classified. pH: 7

Serious eye damage/irritation	:	Not classified. pH: 7
Respiratory or skin sensitization	:	Not classified
Germ cell mutagenicity	:	Not classified.
Carcinogenicity	:	Not classified.
Reproductive toxicity	:	Not classified
Specific target organ toxicity – single exposure	:	Not classified.
Specific target organ toxicity – repeated exposure	:	Not classified
Aspiration hazard	:	Not classified
Symptoms/effects after inhalation	:	May cause respiratory irritation.
Symptoms/effects after skin contact	:	Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	:	Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	:	Gastrointestinal complaints.
Likely routes of exposure	:	Skin and eye contact;Ingestion;Inhalation

SECTION 12: Ecological information

12.1. Toxicity
No additional information available

12.2. Persistence and degradability
No additional information available

12.3. Bioaccumulative potential
No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description	:	UN1950 Aerosols flammable, (each not exceeding 1 L capacity), 2.1
UN-No.(DOT)	:	UN1950
Proper Shipping Name (DOT)	:	Aerosols flammable, (each not exceeding 1 L capacity)
Class (DOT)	:	2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	:	2.1 - Flammable gas

DOT Packaging Non Bulk (49 CFR 173.xxx)	:	None
DOT Packaging Bulk (49 CFR 173.xxx)	:	None
DOT Special Provisions (49 CFR 172.102)	:	N82
DOT Packaging Exceptions (49 CFR 173.xxx)	:	306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	150 kg
DOT Vessel Stowage Location	:	A
DOT Vessel Stowage Other	:	25 - Shade from radiant heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information
Other information : When transported by ground, this product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

ADR
No additional information available

Transport by sea

UN-No. (IMDG)	:	UN1950
Proper Shipping Name (IMDG)	:	Aerosols, Ltd. Qty.
Class (IMDG)	:	2.1 - Flammable gases

Air transport

UN-No. (IATA)	:	UN1950
Proper Shipping Name (IATA)	:	Aerosols, Ltd. Qty.
Class (IATA)	:	2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H340	May cause genetic defects
H350	May cause cancer

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.