



CONCRETE CLEANER & ETCHER

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.
May cause respiratory irritation.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

CONCRETE CLEANER & ETCHER



P.O. BOX 245013
MILWAUKEE, WI 53224
800.776.7192
WWW.SHARECORP.COM



Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. Call a doctor, a POISON CENTER if you feel unwell.

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

CONCRETE CLEANER & ETCHER is specially formulated for cleaning, etching and bleaching concrete, masonry, brick and flagstone. It is a liquid concentrate, easy to dilute and use. **CONCRETE CLEANER & ETCHER** cleans and etches old concrete floors to provide the best surface preparation for maximum paint bonding, and neutralizes alkali present in new concrete.

DIRECTIONS

For heavily soiled concrete, scrub the surface using a water-soluble degreaser to remove soil, grease or oil deposits, then rinse thoroughly. Dilute 1 gallon of **CONCRETE CLEANER & ETCHER** with up to 5 gallons of water depending upon age and condition of the surface. Start with one subsection of the surface to be treated, scrub this solution on the surface with a stiff bristled broom or brush. When bubbling and fizzing has stopped, cleaning and etching process is finished. The acid solution may then be squeegeed to the next area to be treated. Flush area with clean water and allow to dry completely before sealing or painting.

NFPA® Ratings

Health: 3; Flammability: 0; Reactivity: 0

Contains/CAS Number:

Water/7732-18-5; Hydrochloric Acid/7647-01-0;
Surfactant/Proprietary; Tallow Alkyldiamine
Ethoxylate/61790-85-0; Acid Blue 93/28983-56-4

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0140.050115