



FREE FLOAT OWS

CONCENTRATED CLEANER AND DEGREASER

DESIGNED EXCLUSIVELY FOR USE IN OIL/WATER SEPARATOR SYSTEMS.

CONTAINS NO ACIDS, ALKALIES, OR BUTYL SOLVENTS.

WARNING

Causes skin irritation. Causes serious eye irritation.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: □ 1 □ 5 □ 20 □ 35 □ 55 Gallon(s)

FREE FLOAT OWS



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**

WARNING:

Causes skin irritation. Causes serious eye irritation.

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF ON SKIN:

Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



WARNING:

This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Avoid costly sewer discharge violations and eliminate environmental contamination with **FREE FLOAT OWS**. This concentrated cleaner and degreaser has been developed specifically for use in Oil/Water Separator (OWS) systems.

Most detergents emulsify fats, oils, and grease (FOG) and hold them in suspension indefinitely, allowing the FOG to pass through OWS systems and into the sewer lines. Other detergents require drastic pH adjustments or other chemical processes in order for the detergent to release the emulsified FOG.

FREE FLOAT OWS has been formulated with specially selected surfactants that effectively and efficiently lift dirt, grease, oil, and other surface contamination from any water washable surface. Once collected and sent to an OWS system, **FREE FLOAT OWS** easily releases the emulsified FOG, allowing it to coalesce into a separate oil layer, while dirt and other debris are filtered out in the silt chamber or other applicable filtration method.

DIRECTIONS

Inject 2 to 4 ounces of **FREE FLOAT OWS** per gallon of water into the wash system. Wash surface, allow cleaner to work for a few minutes, then rinse. Collect and send rinseate through OWS system. Collect free floating FOG using absorbent pads or brooms. If bioremediation is chosen as a means of handling FOG disposal, **FREE FLOAT OWS** will not interfere with the action of the microbes or otherwise inhibit the bioremediation process.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Alcohol Ethoxylate (68991-48-0); Sodium Tripolyphosphate (7758-29-4); Sodium Metasilicate (6834-92-0); Ethoxylated Alcohols Phosphate Ester (68130-47-2).



Please Recycle.

0414.022618