

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation.

KEEP OUT OF REACH OF CHILDREN NET CONTENTS: □ 1 □ 5 □ 20 □ 35 □ 55 Gallon(s)

PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com



Keep only in original container. Do not breathe mist, spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wearleye protection, protective

IASWALLOWED: ringe mouth to NOT induce vomiting

inutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. Call a doctor, a POISON CENTER if you feel

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

For industrial and commercial use only. For additional information, see Safety Data Sheet,

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.



Removes scum and slime, lime, minerals and scale from hard surfaces such as metal or tile swimming pools, shower walls and floors. Prepares pool surfaces for painting.

DIRECTIONS

Dilute 1 part of **OX-OFF POOL CLEANER** with 3 to 5 parts water, depending upon amount of scale and speed required to perform the job. Apply this solution with sponge or mop to walls and floor. Allow to act for about 5 minutes then rinse thoroughly with water. Stubborn deposits may require a second treatment. For use in high pressure washers, Dilute **OX-OFF POOL CLEANER** with 3 to 5 parts water.

NFPA® Ratings

Health: 3: Flammability: 0: Reactivity: 0

Contains/CAS Number:

Water/7732-18-5; Hydrochloric Acid/7647-01-0; Surfactant/Proprietary; Tallow Alkyldiamine Ethoxylate/61790-85-0; Acid Blue 93/28983-56-4

Dispose of contents/container to comply with local/ regional/national/international regulations.



0140.050515