Safety Data Sheet



SECTION 1: Product and company identification

Product name : Wizzard Aerosol

Use of the substance/mixture : Cleaner Product code : 841001

Company : Share Corporation P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Compressed gas H280 Eye Irrit. 2A H319 STOT SE 3 H336

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02





GHS07

GHS04

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Causes serious eye irritation May cause drowsiness or dizziness

Precautionary statements (GHS-US) : Keep away from hot surfaces, heat, open flames, sparks. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Avoid breathing gas, mist, spray, vapors

Wash thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear eye protection, protective clothing, protective gloves

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Call a doctor, a POISON CENTER if you feel unwell If eye irritation persists: Get medical advice/attention Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Store in a well-ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

oim. initiatio			
Name	Product identifier	%	Classification (GHS-US)
2-propanol	(CAS No) 67-63-0	10 - 30	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			STOT SE 3, H336

 Date of issue: 11/12/2015
 Revision date: 04/09/2015
 Version: 1.0
 P GHS SDS
 Page 1 of 6





Name	Product identifier	%	Classification (GHS-US)
Diethylene Glycol Monoethyl Ether	(CAS No) 111-90-0	5 - 10	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
Butane	(CAS No) 106-97-8	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
Propane	(CAS No) 74-98-6	1 - 5	Flam. Gas 1, H220 Compressed gas, H280

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. Respiratory

problems: consult a doctor/medical service.

First-aid measures after skin contact : Take off contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes serious eye irritation.

Symptoms/injuries after inhalation : No effects known.

Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating. Causes serious eye irritation.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Dry chemical powder. Carbon dioxide. Foam.

5.2. Special hazards arising from the substance or mixture

Reactivity : The product is non-reactive under normal conditions of use, storage and transport. Upon

combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Use water spray or fog for

cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor

nozzles, if possible. If not, withdraw and let fire burn out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air.

May accumulate in low areas e.g. close to the ground. Eliminate every possible source of ignition.

Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment. DO NOT touch spilled material.

Emergency procedures : Ventilate the area thoroughly, especially low lying areas (basements, work pits etc.). Advice local

authorities if considered necessary.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent runoff from entering drains, sewers or waterways. Avoid discharge to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate every possible source of ignition. Keep combustibles (wood, paper, oil, etc.) away from

spilled material. Stop leak if safe to do so. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent the product from entering drains or confined areas. For further information refer to section 8: Exposure-controls/personal protection"".

Methods for cleaning up : Take up liquid spill into absorbent material.

6.4. Reference to other sections

No additional information available

Date of issue: 11/12/2015 Revision date: 04/09/2015 Version: 1.0 P GHS SDS Page 2 of 6

Safety Data Sheet



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not use if spray button is missing or defective. Do not spray on a naked flame or any

incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Do not re-use empty containers. Use only outdoors or in a well-ventilated area. Use personal protective equipment as

required

Hygiene measures : Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush. Take precautionary measures against

static discharge.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Refrigerate.

Incompatible products : Strong oxidizing agents.

Incompatible materials : Heat sources. Sources of ignition.

Storage area : Aerosol 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm
2-propanol (67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	400 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair
propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

Personal protective equipment

Gloves. Protective clothing. Safety glasses. Use appropriate personal protective equipment when risk assessment indicates this is necessary.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Aerosol.

Odor : characteristic

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : 115.6 °F estimate - liquid portion

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : No data available

Date of issue: 11/12/2015 Revision date: 04/09/2015 Version: 1.0 P GHS SDS Page 3 of 6

Safety Data Sheet

SHARE

Relative density : No data available Relative vapor density at 20 °C : No data available

Specific gravity / density : 0.86 g/ml estimate - liquid portion

Solubility : Not determined. Log Pow : No data available Log Kow No data available Auto-ignition temperature : No data available Decomposition temperature No data available Viscosity : No data available : No data available Viscosity, kinematic Viscosity, dynamic No data available

VOC content : 21.82 % estimate - liquid portion

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Diethylene Glycol Monoethyl Ether (111-90-0)		
LD50 oral rat	1920 mg/kg	
2-propanol (67-63-0)		
LD50 oral rat	5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg bodyweight; Rat)	
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)	
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)	
ATE CLP (oral)	5045.000 mg/kg body weight	
ATE CLP (dermal)	12870.000 mg/kg body weight	
ATE CLP (vapors)	73.000 mg/l/4h	
ATE CLP (dust, mist)	73.000 mg/l/4h	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

2-propanol (67-63-0)	
14.00	

IARC group 3 - Not Classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified Symptoms/injuries after inhalation : No effects known.

Date of issue: 11/12/2015 Revision date: 04/09/2015 Version: 1.0 P GHS SDS Page 4 of 6

Safety Data Sheet

SHARE

Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating. Causes serious eye irritation.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

use.

SECTION 12: Ecological information

12.1. Toxicity

2-propanol (67-63-0)		
LC50 fish 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)	
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)	
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)	
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)	
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)	
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)	

12.2. Persistence and degradability

2-propanol (67-63-0)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.	
Biochemical oxygen demand (BOD)	1.19 g O □/g substance	
Chemical oxygen demand (COD)	2.23 g O □/g substance	
ThOD	2.40 g O ☐/g substance	
BOD (% of ThOD)	0.49 % ThOD	

12.3. Bioaccumulative potential

2-propanol (67-63-0)	
Log Pow	0.05 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with

local/regional/national/international regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport hazard class(es) (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306 173.xxx)

DOT Quantity Limitations Passenger : 75 kg

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft : 150 kg

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

Date of issue: 11/12/2015 Revision date: 04/09/2015 Version: 1.0 P GHS SDS Page 5 of 6

Safety Data Sheet



DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol	CAS No 67-63-0	10 - 30
butane (106-97-8)		
Not listed on SARA Section 313 (Specific toxic cher	nical listings)	
2-propanol (67-63-0)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
propane (74-98-6)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		

California Proposition 65 - This product does not contain a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness


NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury

unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Date of issue: 11/12/2015 Revision date: 04/09/2015 Version: 1.0 P GHS SDS Page 6 of 6