



# HEAVY DUTY LIQUID DRAIN OPENER

**SULFURIC ACID  
DRAIN SOLVENT**

**DANGER**

Harmful if swallowed. Causes severe skin burns and eye damage. May cause cancer.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: ONE QUART (32 fl. oz.)**



**DANGER:**

Harmful if swallowed. Causes severe skin burns and eye damage. May cause cancer.

**PREVENTION:**

Do not handle until all safety precautions have been read and understood. Wear protective gloves and goggles/face shield. Do not breathe vapors or mist. Wash face, hands and any exposed skin thoroughly after handling.

**DO NOT** mix or dilute with water or any chemicals.

**DO NOT** transfer contents into any other container.

**DO NOT** use a plunger when this product is in drain lines.

**DO NOT** use in combination with any other chemical drain openers.

**DO NOT** use in drains containing a build-up of plaster waste material because a toxic gas may be released.

**DO NOT** allow this product to stand on porcelain, or contact any enamel, aluminum or chrome.

**DO NOT** attempt to disassemble plumbing or remove clean-out plug(s) from lines containing this product.

**DO NOT** use in rusted or leaking pipes.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

**IF ON SKIN (OR HAIR):** Rinse area with water/shower. Take off immediately all contaminated clothing.

**IF SWALLOWED:** Call Poison Control/Emergency Services immediately.

**IF INHALED:** Move exposed person to fresh air. Call emergency services immediately.

Store in a locked area to prevent any unauthorized use. Always use in a well ventilated area.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**HEAVY DUTY LIQUID DRAIN OPENER** is intended for use by plumbers and other qualified maintenance personnel. It is not for home use or retail sale. It quickly dissolves organic obstructions, grease, hair, sanitary napkins, rags, sludge, soap, paper, food, etc. in drains or sinks, toilets and grease traps.

Always use with good ventilation. After pouring **HEAVY DUTY LIQUID DRAIN OPENER** slowly into drain immediately place an upside-down bucket, dishpan, or deep container over the drain to protect from possible splash back.

**FOR COMPLETELY CLOGGED DRAINS:** Remove standing water before pouring. Pour 4 ounces of **HEAVY DUTY LIQUID DRAIN OPENER** into drain. Using more than 4 ounces could generate excessive heat causing toilet bowls to crack. Allow to stand for 15 minutes. Carefully and slowly add 4 ounces of water. Wait 5 minutes, then slowly run cold water. If the drain is still clogged, repeat this process.

**FOR PARTIALLY CLOGGED (SLOW) DRAINS:** Pour 4 ounces of **HEAVY DUTY LIQUID DRAIN OPENER** and let stand for 5 minutes. Repeat this procedure. Flush several times with cold water.

**NFPA® RATINGS**

Health: 3; Flammability: 0; Reactivity: 2

**INGREDIENTS/CAS #:**

Sulfuric Acid (7664-93-9); Water (7732-18-5)

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**WARNING:**

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.



Please Recycle.