

H.D. MULTI-PURPOSE GREASE

Lithium Complex Extreme Pressure Grease

Form: Semi-Solid

Color: Blue

Odor: Mild

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

Flash Point (°F): N/D

Specific Gravity: 7.51 lbs/gal

Density: 0.9 g/cm³

Storage Stability (at 70°F): 1 year

Great for use in...

- **Industrial Applications**
- **Automotive Applications**
- **Mining Applications**
- **Shock Loading Applications**
- **Water Pumps**
- **Bushings**
- **Slides**
- **Gears**
- **Bearings**
- **Press Rolls**
- **Chassis Points**
- **Disk Brake Systems**

TYPICAL SPECIFICATIONS

NLGI Grade	2
Color	Blue
Thickener Type	Lithium Complex
Viscosity @ 40°C, cSt	180-240
Viscosity @ 100°C, cSt	16.5-19.0
Viscosity Index, Min	90
Operating Temperature Range	-30°F to 325°F
Penetration Worked	265-295
Dropping Point (°F).....	500+
Timken OK Load (lbs)	60
4 Ball EP Weld Point, kgf.....	315

HMIS®			NFPA		
Health	1	Severe 4	Extreme	Health.....	1
Flammability	1	Serious 3	High	Flammability	1
Physical Hazard	0	Moderate 2	Moderate	Reactivity	0
Personal Protection	X	Slight 1	Slight	Special Precautions	None
		Minimal 0	Insignificant		